



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® 2in1 Wall & Ceiling Spray Texture: Knockdown Water Based

PRODUCT DESCRIPTION

DAP® 2in1 Wall & Ceiling Knockdown Water Based is an innovative technology system that allows you to tackle wall, ceiling & hard to reach areas with just one can. DAP's Aim Tech nozzle can be easily rotated upwards to spray at almost any angle achieving maximum coverage. Its ergonomic system provides professional hopper results and ultimate spray control. The aerosol can is extremely easy to use, offers a wide fan for even coverage without excessive dripping or clogging. Proven to create a seamless blend with existing textured surfaces by adjusting the texture size to your desired finish. Fast dry time of 30 minutes. Excellent paintability; no priming needed and won't soften or drag. Interior/Exterior.

PACKAGING	COLOR	UPC
25 oz can	White	7079850010

KEY FEATURES & BENEFITS

- Ideal for vertical, overhead and hard to reach areas
- Wide coverage with even spray application
- Excellent match to textured surfaces
- 30 minute paint ready time
- Strong and durable cure
- Low odor
- Easy water clean-up
- Interior/exterior

SUGGESTED USES

USE FOR REPAIRING TEXTURED SURFACES:

- Drywall
- Stucco
- Plaster



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- Shake well before spraying
- Apply in temperatures above 40°F
- Spray using intermittent bursts
- Dispense a quick burst on scrap material to activate pressure
- Practice applying on scrap material before use
- Dip putty knife in water before each knockdown stroke
- Store away from direct heat in temperatures ranging from 40°F to 90°F

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material.

Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture.

Product Application

1. **UNLOCK** tab by bending backwards. THIS IS A RE-LOCKING TAB AND NOT MEANT TO BE BROKEN OFF.
2. **ADJUST** nozzle upward to desired spray angle, nozzle can rotate up to 60 degrees. BE SURE TO POINT AWAY FROM FACE AND PEOPLE.
3. **TWIST** nozzle to desired texture size fine, medium, or heavy.
4. **SHAKE** can upside down **vigorously** for more than one minute after hearing mixing marble moving freely in the can. **IMPORTANT** Dispense a quick burst of material on scrap materials to activate before applying to surface.
5. **SPRAY** holding can approximately 12 to 18 inches away from surface using intermittent bursts, sweeping across the repair in a quick, continuous motion. For superior blending, feather texture into surrounding repair area using the can. Add coverage as needed to match texture density. If not satisfied, scrape off and reapply. **IMPORTANT** be sure that the area is well ventilated and proper safety gear is worn.
6. **KNOCKDOWN:** Allow spray texture to dry: immediately for fine, 30 secs to 1 minute for medium and 1-2 minutes for heavy. Hold putty knife parallel to the wall or ceiling and lightly flatten knockdown to desired texture. **IMPORTANT** be sure to dip putty knife into water in between each knockdown.
7. **PAINT**, allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior applications, use an exterior grade paint.
8. **CLEAN-UP** tools and area with towel and warm water. Place nozzle in the upright position, invert can, point the top straight down. Spray onto a disposable surface until no texture sprays outs. Be sure to remove any texture build up from tip/nozzle to prevent material drying on tip/nozzle.
9. **STORE:** adjust spray angle to starting position and re-lock using tab.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	White textured material
Base Polymer	Acrylic Latex
Weight % Solids	55.6%
Density (lbs per gallon)	10.9
Odor	Low odor
Clean Up	Water
Shelf Life	12 months
Coverage	Fine: up to 130 sq. ft. Medium: up to 90 sq. ft. Heavy: up to 70 sq. ft.
Typical Application Properties	
Application Temperature Range	Best between 65°F-80°F
Typical Cured Performance Properties	
Service Temperature Range	Above 40°F

CLEAN UP & STORAGE

Uncured material can be cleaned up with soap and water. Excess cured material can be scraped off or sanded down.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty: If product fails to perform as directed within one year from the date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com