



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® FAST DRY High Strength Spackling

PRODUCT DESCRIPTION

DAP® FAST DRY High Strength Spackling is a professional-grade spackling compound uniquely formulated to provide strength and fast drying capabilities allowing some repairs to be painted in as little as 15 minutes. Its ready-to-use, smooth formula spreads easily and won't sink, shrink or crack, typically filling repairs in one coat. DAP® Fast Dry High Strength Spackling is 3X stronger** with superior impact resistance over traditional spackling compounds.



PACKAGING	COLOR	UPC
16 fl. oz. (473 mL)	Off-White	7079818440
32 fl. oz (846 mL)	Off-White	7079818441

KEY FEATURES & BENEFITS

- Ideal for large drywall repairs
- 8X* Faster Finish - 15-minute paint ready on repairs 1" x 1/8" in depth or smaller, depending on temperature and humidity
- 3X** Stronger – Superior Impact Resistance
- 1 Coat Application for repairs 1" wide by 1/8" in depth – Won't sink or shrink
- No priming required – Won't flash paint
- Easy-to-use, latex-based formula
- Easy water clean-up & low odor
- Interior/Exterior use

*Than traditional heavyweight spackling.

** Than other spackling compounds.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

Ideal for filling holes, cracks, dents, defects and larger repairs in drywall and plaster.

FOR BEST RESULTS

If spackling seems dry when opening, stir completely and evenly until it's a smooth, creamy consistency.

Do not apply when temperatures are below 40°F.

Do not apply outside if rain is expected within 24 hours.

DO NOT USE AS A SKIM COAT.

For exterior applications, always topcoat with high quality exterior-grade paint before moisture contact.

APPLICATION

APPLICATION:

1. Surface must be clean, dry, structurally sound, and free of all foreign material. De-gloss surface, if necessary, for better adhesion to drywall surface.
2. If spackling seems dry when opening, stir completely and evenly until it's a smooth, creamy consistency.
3. Apply with a clean putty knife.
4. For a smooth finish, dip putty knife in water and lightly smooth spackling.
5. One application is usually sufficient for repairs 1" wide x 1/8" in depth.
6. May be painted in as little as 15 minutes on repairs 1" x 1/8" in depth or smaller, depending on temp., humidity and depth of fill. If sanding, additional dry time may be needed, approximately 60 minutes for repairs 1" x 1/8" in depth or smaller. If sanding is required, use medium-grit sandpaper and finish with fine-grit for a smooth finish. Wet sanding is recommended to avoid generation of dust.
7. Paint with latex or oil-based paints. Ensure that DAP® FAST DRY High Strength Spackling is thoroughly dry before applying oil-based paint.
8. Clean tools immediately with water. Dry material must be cut or scraped away.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Thick Paste; contents may appear dry when opening.
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Weight/Gallon	5.01-5.11 lbs./gal
Solids	63%
Application Temperature	Do not apply when temperatures are below 40°F
Service Temperature	0°F to 150°F
Shelf Life	12 months
Flash Point	100°C
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	15 min time to paint (1/8" depth, depending on temperature, humidity)

CLEAN UP & STORAGE

Clean tools immediately with water. Dry Material must be cut or scrapped away. Be sure container is closed and tightly sealed. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling 888-DAP-TIPS.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

Limited Warranty: If product fails to perform when used as directed within one year of date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damage.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com