

Safety Data Sheet

24 Hour Emergency Phone Numbers Medical/Poison Control:

In U.S.: Call 1-800-222-1222

Outside U.S.: Call your local poison

control center

Transportation/National Response Center:

1-800-535-5053 1-352-323-3500

NOTE: The National ResponseCenter emergency numbers to be used only in the event of chemical emergencies involving a spill, leak, fire, exposure or accident involving chemicals.

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

1. Identification

Product Name: Touch N Foam Professional Foam Kit 600

1.75 PCF Low GWP A Side

Product UPC Number: 10075650626099

Manufacturer: DAP Global Inc.

2400 Boston Street Suite 200 Baltimore, MD 21224-4723

888-327-8477 (non - emergency matters)

SDS Coordinator: MSDS@dap.com

Emergency Telephone:

Transportation: 1-800-535 -5053

1-352-323-3500

Poison Control: 1-800-222-1222

Revision Date: 5/10/2024

Supercedes Date: 4/12/2022

Product Use/Class: Foam Sealant/Adhesive

SDS No: 4756701

Preparer: Regulatory and Environmental

Affairs

2. Hazards Identification

EMERGENCY OVERVIEW: Contents under pressure. Do not puncture can. Exposure to temperatures above 120 'F may cause can to rupture. The primary adverse health effects of this product are related to the Polymeric Isocyanate (MDI) component. Therefore, adequate ventilation should be provided to avoid exceeding the exposure limits of these components (See Section 8). MDI vapor can irritate the respiratory tract causing runny nose, sore throat, coughing and reduce lung function.

GHS Classification

Acute Tox. 4 Inhalation, Carc. 2, Eye Irrit. 2A, Gas under Pressure, Comp. Gas, Resp. Sens. 1, Skin Irrit. 2, Skin Sens. 1, STOT RE 2, STOT SE 3 RTI

Symbol(s) of Product







Signal Word

Danger

Possible Hazards

20% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Compressed Gas	H280	Contains gas under pressure; may explode if heated.
Skin Irritation, category 2	H315	Causes skin irritation.
Skin Sensitizer, category 1	H317	May cause an allergic skin reaction.
Eye Irritation, category 2A	H319	Causes serious eye irritation.
Acute Toxicity, Inhalation, category 4	H332	Harmful if inhaled.
Respiratory Sensitizer, category 1	H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
STOT, single exposure, category 3, RTI	H335	May cause respiratory irritation.
Carcinogenicity, category 2	H351	Suspected of causing cancer.
STOT, repeated exposure, category 2	H373	May cause damage to organs through prolonged or repeated exposure.

GHS LABEL PRECAUTIONARY STATEMENTS

P201 Obtain special instructions before use.

P260 Do not breathe dust/fume/gas/mist/vapours/spray.

P264 Wash thoroughly after handling.

P271 Use only outdoors or in a well-ventilated area.

P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

P281 Use personal protective equipment as required.

P284 [In case of inadequate ventilation] wear respiratory protection.

P302+P352 IF ON SKIN: Wash with plenty of soap and water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Get medical advice/attention.
P312 Call a POISON CENTER or doctor/physician if you feel unwell.

P321 Specific treatment (see ... on this label).

P332+P313 If skin irritation occurs: Get medical advice/attention.
P333+P313 If skin irritation or rash occurs: Get medical advice/attention.
P337+P313 If eye irritation persists: Get medical advice/attention.

P342+P311 If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

P362 Take off contaminated clothing.

P403+P233 Store in a well-ventilated place. Keep container tightly closed.

P405 Store locked up.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

P501 Dispose of contents/container.

GHS SDS PRECAUTIONARY STATEMENTS

P363 Wash contaminated clothing before reuse.

3. Composition/Information on Ingredients

Chemical NameCAS-No.Wt. %GHS SymbolsGHS StatementsPolymeric diphenylmethane diisocyanate9016-87-945-70GHS07-GHS08H315-317-332-334-335

4,4'-Methylene diphenyl diisocyanate (MDI)

101-68-8

10-30 GHS07-GHS08

H315-317-319-332-334-335-351
-373

Hydrofluoroolefins

29118-24-9

10-30 No Information
No Information
P-Butyne-1,4-diol, polymer with (chloromethyl)

68441-62-3

5-10 GHS07

H302-319

2-Butyne-1,4-diol, polymer with (chloromethyl) oxirane, brominated, dehydrochlorinated,

methoxylated

Tris(2-chloro-1-methylethyl) phosphate 13674-84-5 3-7 GHS07 H302

Hydrofluroolefins 102687-65-0 1-5 No Information No Information

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist. Use a rag to remove excess foam from skin and remove contaminated clothing. Use of a solvent, such as acetone (nail polish remover) or mineral spirits, may help in removing uncured foam residue from clothing or other surfaces (avoid eye contact). Cured foam may be physically removed by persistent washing with soap and water. If irritation develops, use mild skin cream. If irritation persists, obtain medical attention.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: Closed containers may burst if exposed to extreme heat or fire. Containers may explode if exposed to extreme heat.

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Water Spray or Fog, Water

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Use personal protective equipment as necessary. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers. Uncured product is very sticky, so carefully remove the bulk of the foam by scraping it up and then immediately remove residue with a rag and solvent such as polyurethane cleaner, mineral spirits, acetone (nail polish remover), paint thinner, etc. Once the product has cured, it can only be removed physically by scraping, buffing, etc. Dispose as plastic waste (foam plastic) in accordance with all applicable guidelines and regulations.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Make sure nozzle is directed away from yourself prior to discharge. Keep away from open flames, hot surfaces and sources of ignition. Wear appropriate personal protection. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Ensure fresh air entry during application and drying. Wash thoroughly after handling. Contains isocyanates. See information supplied by the manufacturer. Persons allergic to isocyanates, and particularly those suffering from asthma or other respiratory conditions, should not work with isocyanates.

STORAGE: Store away from sources of ignition and heat. Protect material from direct sunlight. Keep containers tightly closed in a dry, cool and well-ventilated place. Do not store at temperatures above 120 °F (49 °C). Store containers away from excessive heat and freezing. Store away from caustics and oxidizers.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits

<u>Chemical Name</u> <u>ACGIH TLV-TWA</u> <u>ACGIH-TLV STEL</u> <u>OSHA PEL-TWA</u> OSHA PEL-CEILING

Polymeric diphenylmethane diisocyanate N.E. N.E. N.E. N.E. N.E.

4,4'-Methylene diphenyl diisocyanate (MDI)	0.005 ppm TWA Methylene bisphenyl isocyanate (MDI)	N.E.	N.E.	0.02 ppm Ceiling, 0.2 mg/m3 Ceiling
Lhadaafhaan alafaa	, ,	N. E	NI E	NI E
Hydrofluoroolefins	N.E.	N.E.	N.E.	N.E.
2-Butyne-1,4-diol, polymer with	N.E.	N.E.	N.E.	N.E.
(chloromethyl)oxirane, brominated,				
dehydrochlorinated, methoxylated				
Tris(2-chloro-1-methylethyl) phosphate	N.E.	N.E.	N.E.	N.E.
Hydrofluroolefins	N.E.	N.E.	N.E.	N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: Use a NIOSH approved full facepiece organic vapor cartridge respirator. If concentrations exceed the exposure limits specified, use of a NIOSH-approved supplied air respirator is recommended. Where the protection factor is exceeded, use of a Self Contained Breathing Apparatus (SCBA) may be necessary. A respiratory protection program that meets the OSHA 1910.134 and ANSI Z88.2 requirements must be followed whenever workplace conditions warrant a respirator's use.



SKIN PROTECTION: Wear nitrile, neoprene, or natural rubber gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Provide eyewash and solvent impervious apron if body contact may occur.



HYGIENIC PRACTICES: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

Vapor Pressure, mmHg:

Flash Method:

9. Physical and Chemical Properties

 Color:
 Cream
 Appearance:
 Foam

 Odor:
 Slight Solvent
 Physical State:
 Foam

 Density, g/cm3:
 1.21 - 1.22
 Odor Threshold:
 Not Established

Freeze Point, °C: Not Established pH: Not Applicable
Solubility in Water: Not Established Viscosity (mPa.s): Not Applicable
Decomposition Temperature, °C: Not Established Partition Coeff., n-octanol/water: Not Established

Boiling Range, °C: N.A. Aerosol, foam. Explosive Limits, %: N.E.

Flash Point, °C: Aerosol or foam, not Auto-Ignition Temperature, °C Not Established

applicable.

Evaporation Rate: Faster Than n-Butyl Acetate

Vapor Density: Heavier Than Air

Combustible Dust: Does not support combustion

(See "Other information" Section for abbreviation legend)

(If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: Stable under recommended storage conditions.

CONDITIONS TO AVOID: Excessive heat and freezing.

Not Established

Not Applicable

INCOMPATIBILITY: Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: Vapors may be irritating to eyes, nose, throat, and lungs. Inhalation of high concentrations may cause headache, nausea, and dizziness.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: May cause sensitization by skin contact. May cause localized irritation, reddening or swelling. Prolonged or repeated exposure may lead to sensitization and/or contact dermatitis. This product has strong adhesive-like characteristics and will adhere aggressively to skin and other surfaces. If accidental contact occurs, follow the appropriate first-aid procedure described in Section 4 of this SDS.

EFFECT OF OVEREXPOSURE - EYE CONTACT: Direct eye contact may cause irritation. Mist and vapors may cause eye irritation. Foam contact can cause physical damage due to adhesive character.

EFFECT OF OVEREXPOSURE - INGESTION: Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea.

CARCINOGENICITY: Limited evidence in experimental animals.

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause respiratory system damage. Repeated contact may cause allergic reactions in very susceptible persons.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Inhalation, Eye Contact

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u> 9016-87-9	<u>Chemical Name</u> Polymeric diphenylmethane diisocyanate	Oral LD50 49000 mg/kg Rat	Dermal LD50 >9400 mg/kg Rabbit	Vapor LC50 N.I.
101-68-8	4,4'-Methylene diphenyl diisocyanate (MDI)	31600 mg/kg Rat	9400 mg/kg Rabbit	N.I.
29118-24-9	Hydrofluoroolefins	N.I.	N.I.	N.I.
68441-62-3	2-Butyne-1,4-diol, polymer with (chloromethyl)oxirane, brominated, dehydrochlorinated, methoxylated	N.I.	N.I.	N.I.
13674-84-5	Tris(2-chloro-1-methylethyl) phosphate	1500 mg/kg Rat	>5000 mg/kg Rabbit	N.I.
102687-65-0	Hydrofluroolefins	N.I.	N.I.	N.I.

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: No Information

13. Disposal Information

DISPOSAL INFORMATION: Contents under pressure. Dispose of material in accordance with all federal, state and local regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Liquids cannot be disposed of in a landfill. Before disposing of containers, relieve container of any remaining product and pressure. Empty cylinders, once relieved of all pressure, can be disposed of as non-hazardous waste.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: Contain spilled material and remove with inert absorbent. Dispose of contaminated absorbent, container and unused contents in accordance with local, state and federal regulations. Use personal protective equipment as necessary. Read all product instructions before using. Personal protective equipment should include impervious gloves, protective eye wear, and suitable work clothes. Scrape up dried material and place into containers. Uncured product is very sticky, so carefully remove the bulk of the foam by scraping it up and then immediately remove residue with a rag and solvent such as polyurethane cleaner, mineral spirits, acetone (nail polish remover), paint thinner, etc. Once the product has cured, it can only be removed physically by scraping, buffing, etc. Dispose as plastic waste (foam plastic) in accordance with all applicable guidelines and regulations.

14. Transport Information

DOT UN/NA Number: UN3500

DOT Proper Shipping Name: Chemical under pressure, n.o.s.

DOT Technical Name: (trans-1,3,3,3-Tetrafluoroprop-1-ene, trans-1-Chloro-3,3,3-trifluoropropene)

DOT Hazard Class: 2.2 Non-flamm compressed gas

Hazard SubClass: N.A.
Packing Group: N.A.

SPECIAL TRANSPORT PRECAUTIONS: No Information

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Gas under pressure, Carcinogenicity, Acute Toxicity (any route of exposure), Skin Corrosion or Irritation, Respiratory or Skin Sensitization, Serious eye damage or eye irritation, Specific target organ toxicity (single or repeated exposure)

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

Chemical NameCAS-No.Polymeric diphenylmethane diisocyanate9016-87-94,4'-Methylene diphenyl diisocyanate (MDI)101-68-8

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt.

This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

16. Other Information

Revision Date: 5/9/2024 Supersedes Date: 4/12/2022

Reason for revision: Product Composition Changed

Substance Hazard Threshold % Changed Substance Chemical Name Changed

Substance and/or Product Properties Changed in Section(s):

02 - Hazards Identification 05 - Flammability Information 09 - Physical & Chemical Information 11 - Toxicological Information Revision Statement(s) Changed

Datasheet produced by: Regulatory Department

HMIS Ratings:

Health: Flammability: Reactivity: Personal Protection:

2* 1 0 X

VOC Less Water Less Exempt Solvent, g/L: 0.3

VOC Material, g/L: 0

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 8.66

VOC Actual, Wt/Wt%: 0.0

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H302	Harmful if swallowed.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled.
H335	May cause respiratory irritation.
H351	Suspected of causing cancer.
H373	May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

We believe the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.