



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 4/13/04

DAP® PLASTIC WOOD® Wood Filler

- Acts like real wood
- Sandable and stainable
- Non-Shrinking

Packaging: 4 fl oz. Can, 1.87 oz. tube, 8 oz. can, 16 oz. can, 2.5 lb. can, 10 lb. can

Colors: White, Natural, Light Oak, Pine, Golden Oak, Red Oak, Red Mahogany, Maple, Walnut

UPC Numbers: 21144, 21400, 21404, 21408, 21412, 21420, 21424, 21430, 21434, 21500, 21502, 21504, 21506, 21508

Company Identification:

Manufacturer: DAP Inc.

Marketed by: DAP Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.

Order Information: 800-327-3339

Fax Number: 410-534-2650

Also, visit the DAP website at www.dap.com.

Product Description:

DAP PLASTIC WOOD is a high-performance cellulose fibre wood filler that hardens to give a surface and body that looks and acts like real wood. PLASTIC WOOD can be sanded, cut, drilled, planed, varnished, painted or lacquered. For use on furniture, doors, paneling, molding, plywood and other wood surfaces Available in popular wood shades

Suggested Uses:

Ideal for repairing surface defects on wooden surfaces such as:

- Furniture
- Paneling
- Molding
- Doors
- Plywood

SURFACE PREPARATION & APPLICATION

- Surface to be filled must be clean and dry.
- If wood is to be stained, stain before filling. Then select the closest color of PLASTIC WOOD to match the stained wood. Stain the wood filler to obtain a finished color.
- For canned products, stir product with putty knife before application.
- If the wood filler has become too stiff or dry, thin with DAP PLASTIC WOOD Solvent.
- Press wood filler firmly into place with a putty knife. Avoid excess contact with surrounding area. Build fill up slightly higher than surface to allow for settling and sanding.
- Let dry thoroughly before sanding or finishing.

FOR BEST RESULTS

- If used in an exterior application, PLASTIC WOOD wood filler must be coated with a high quality coating after it has dried.

Physical & Chemical Characteristics:

Consistency:	Stiff Dough
Base:	Nitrocellulose
Volatile:	Acetone, Isopropanol and n-Butyl Acetate
Filler:	Wood Fiber or Cellulose Fiber
Odor:	Ketone/Alcohol (or strong solvent)
Solids:	58% by weight
Shelf Life:	1 Years Minimum
Drying Time:	1 to 2 hours in shallow fills up to 1/8"; Up to 24 hours in fills 1/4" and over.
Flash Point:	-4°F T.C.C. (-20°C)

Packaging:

<i>UPC</i>	<i>Size</i>	<i>Color</i>
21144	10lb	Natural
21500	1.87 oz	Natural
21502	1/4 lb.	Natural
21400	1/4 lb.	Light Oak
21404	1/4 lb.	Pine
21408	1/4 lb.	Golden Oak
21420	1/4 lb.	Red Oak
21424	1/4 lb.	Red Mahogany
21430	1/4 lb.	Maple
21434	1/4 lb.	Walnut
21412	1/4 lb.	White
21506	16 oz.	Natural
21508	2.5 lb.	Natural
21504	8 oz .	Natural

MSDS No. 79201

Clean Up:

Clean tools immediately after use with mineral spirits. Be sure container lid is closed and tightly sealed. Store in a cool, dry place.

Safety:

See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting www.dap.com or by calling 888-DAP-TIPS.

Warranty Information:

If you are not completely satisfied with the product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston St., Baltimore, MD, 21224, for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.