



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 1/28/08

DAP® Silicone-Be-Gone™ Silicone Remover

- Softens Old Silicone for Easy Removal
- Won't Harm Most Surfaces
- Low Odor
- Fast Acting – Removes Most Silicone Residue in 30 Minutes to 1 Hour.

Packaging: 3 fluid ounces (90 milliliters)
Color: Brown Gel
UPC Number: 7079813330

Company Identification:

Manufactured for: DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP® Silicone-Be-Gone™ Silicone Sealant Remover is a gel that will soften unwanted silicone for easy removal prior to applying fresh sealant. Also excellent for cleaning up areas where unwanted silicone has been applied and cured.

Coverage:

Approximately one bathtub (appx. 10 linear feet of ¼" bead)

Ideal for Use on:

- Porcelain
- Ceramic Tile
- Fiberglass
- Stainless Steel
- Most Plastics
- Glass
- Formica
- Concrete
- Granite
- Chrome Plated Brass

Note: Always test in a inconspicuous area prior to use. Will damage nylon. May damage or discolor some metals, painted and synthetic finishes or treated wood surfaces.

Surface Preparation & Application:

- Wear eye and hand protection.
- Cut back unwanted silicone as close to surface as possible.
- Apply a liberal coat (1/8" to 1/4" build-up) of Silicone-Be-Gone Silicone Remover with brush provided in package.
- Let stand for 30 minutes or until residue softens or begins to lift. Do not allow to dry on the surface. If longer waiting periods are necessary for softening sealant, reapply gel to prevent drying.
- Wipe off with a clean cloth.
- Scrape away any remaining residue.
- Rinse thoroughly cleaning area with soap and water.
- Follow sealant application instructions to reapply new sealant. Surface will now accept different types of sealants including latex or advanced polymer sealants.

FOR BEST RESULTS

- Thicker beads of silicone may require multiple applications or longer waiting periods to soften.
- Store in temperatures between 45°F and 100°F
- To prevent staining, do not allow to dry on surface.
- **Always test in a inconspicuous area prior to use.** Immediately wipe off of any surface not to be treated for silicone removal.

Physical & Chemical Characteristics:

Stand Time:	30 minutes or longer
Odor:	Mild petroleum
Consistency:	Gel
Vehicle:	Petroleum
Flash Point:	180°F
Weight per Gallon:	6.1 lbs
Temperature Application Range:	For best results apply at 60°F to 85°F
Freezing Point:	-22°F
Shelf Life:	1 year in unopened, sealed container
Coverage:	Approximately 10 feet of cut back 1/4" bead
MSDS No:	00017116001

Clean Up:

Remove excess product with a clean cloth. Clean area with soap & water once product & remaining silicone has been scraped away.

Safety:

See product label or Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by calling 888-DAP-TIPS or by visiting our website at www.dap.com.

Warranty Information:

If not satisfied with product performance when used as directed, return used container and sales receipt to DAP Products Inc., Technical Customer Service, 2400 Boston St., Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.

