



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 9/19/11

DAP[®] SEAL 'N PEEL[®] Removable Weatherstrip Caulk

- Temporarily Seals Out Drafts
- Saves Energy
- Weatherproof Seal
- Indoor/Outdoor

Packaging: 10.1 fl. oz. (300ml)
Color: Clear
UPC Number: 7079818354

Company Identification:

Manufactured For: DAP Products Inc., 2400 Boston St., Baltimore, Maryland 21224
Usage Information: Call 1-888-DAP-TIPS or visit dap.com & click on "Ask the Expert"
Order Information: 800-327-3339
Fax Number: 410-534-2650

Product Description:

DAP[®] SEAL 'N PEEL[®] Removable Weatherstrip Caulk is formulated for use as seasonal weather-stripping. It provides a watertight, weatherproof and fast drying seal against air and moisture, keeping homes warmer in winter, cooler in summer, reducing energy bills. Seal drafty windows, seasonally used doors, around air conditioners, vents or fans & then peel away when needed. Interior and exterior use.

Suggested Uses:

Ideal for use on:

- Window and door frames
- Vents and fans
- Patio doors
- Air conditioners

Adheres to:

- Glass
- Painted Surfaces (fully dried, no cracking)
- Ceramics
- Aluminum
- Wood
- Fiberglass
- Drywall
- Concrete
- Metal
- Porcelain

Surface Preparation & Application:

1. Remove any rust and any loose or foreign material.
2. Clean & dry surface. The surfaces must be free of creosote, oil, grease, wax, silicone, silicone-based product, asphalt or bitumen-based product, and any material soluble in solvents.
3. Trim nozzle to desired bead size. Cut the nozzle at a right angle (90°) slightly narrower than the width of the gap.
4. Puncture inner seal.
5. Load into caulking gun.
6. Apply uniform pressure while maintaining a 45° angle between the gun and the gap to fill gaps with caulk.
7. Do not shape or tool the bead.

DO NOT SEAL FIRE EXITS. CONSULT LOCAL FIRE OR CODE OFFICIAL WITH QUESTIONS ABOUT FIRE EXITS.

FOR BEST RESULTS

- Caulk in temperatures above 40°F.
- Store away from extreme heat or cold.
- Not for continuous underwater use.
- Do not use on freshly painted surfaces.
- Do not use on insulating panels or plastic materials which can be damaged by solvents.
- New metal and solvent resistant oily surfaces must be washed with acetone and dried.
- For unusual substrates, perform a test for adhesion prior to use.
- For gaps wider than ¼", a backing rod should be used.
- The sealant should come into contact with each of the surfaces on a width of at least 1/8".
- If applied indoors, the area must be ventilated during application and drying time.
- Product left in place for more than 1 year may be difficult to remove.

Physical & Chemical Characteristics:

Tooling Time:	N/A
Tack Free Time:	10 Minutes
Dynamic Joint Movement:	N/A
Service Expectancy:	Temporary – 12 months maximum
Paintability:	N/A
Odor:	Solvent
Consistency:	Smooth, gunnable paste
Polymer:	Synthetic rubber
Volatile:	Strong aliphatic and aromatic solvents
Flash Point:	80°F (Pensky Martin CC) 82.4 °F (Tag Closed Cup)
Filler:	N/A
Density:	Approximately 6 lbs./gallon
Solids:	Approximately 35% by weight
Temperature Service Range:	-20°F to 122°F
Temperature Application Range:	40°F to 100°F
Freeze/Thaw Stability:	Freeze thaw stable
Shelf Life:	24 months from date of manufacture when stored in unopened container below 85°F
Coverage:	55 linear ft. @ 3/16" diameter bead size or 4 average size windows
MSDS No.:	00077136001

Clean Up:

While wet use a solvent moistened cloth. After the product has dried, excess material may be easily peeled away. Do not use solvent to clean hands.

Safety:

ALLOW FRESH AIR ENTRY DURING APPLICATION & DRYING. This product contains flammable solvents. Do not smoke when using this product. Work in good ventilation conditions. Suppress all flash sources, flames, and intense heat during application and drying. See product label and Material Safety Data Sheet (MSDS) for safety information. You can request an MSDS by visiting our website at dap.com or by calling 1-888-DAP-TIPS.

Warranty Information:

If not satisfied with product performance when used as directed, DAP will either provide a replacement product or sales price refund. Call 1-888-DAP-TIPS, with your sales receipt and product container available, to arrange for warranty fulfillment. DAP will not be liable for incidental or consequential damages.

