



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 9/1/05

DAP® Wood Bleach by PLASTIC WOOD®

- Gently lightens wood
- Excellent for water spots
- Easy to use

Packaging: 12oz
Color: White
UPC Number: 65072

Company Identification:

Manufacturer: DAP Inc., 2400 Boston St., Suite 200, Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP® Wood Bleach by PLASTIC WOOD® is an oxalic acid powder, which when mixed with hot water, produces a bleach for treating uncoated wood. The bleach gently lightens wood without significantly raising wood grain; unlike chlorine based bleaches. DAP® Wood Bleach is excellent for bleaching out black water spots on oak floors.

Suggested Uses:

- *For the gentle lightening of wood surfaces.*
- *Ideal for the removal of dark water stains from wooden floors.*

Surface Preparation & Application:

- Wood to be bleached must be free of all coatings, waxes and oils. Use appropriate paint strippers, wood cleaners, sanding or scraping to remove coatings, waxes and oils.
- Always wear rubber gloves, protective clothing and eye protection when using this product. Dissolve the contents of one package into 1 gallon of hot water. Stir thoroughly until all crystals are completely dissolved.
- Apply the hot solution with a scrub brush or old paintbrush. On larger jobs use a mop. Apply liberally allowing the solution to remain on the surface until it is bleached to the desired lightness. If the solution cools before the job is finished, reheat but do not allow the solution to boil.
- Rinse the bleached surface repeatedly with clean water and allow it to dry. Test the removal of bleach from the dried wood by wiping it with a dark colored cloth. Check for powder residue. If powder persists, rinse the surface again with clean water and allow to dry.
- Sand wood and finish with desired product.

Physical & Chemical Characteristics:

Color:	White Crystals
Solids Content:	100% in granular form
Vehicle:	Dissolved in water
Coverage:	N/A
Consistency:	Dry crystals (oxalic acid)
Drying Time:	Accomplished by penetration and evaporation
Hazardous Ingredients:	Contains 100% oxalic acid, avoid contact with silver and sodium chlorite.
MSDS #:	79208

Clean Up:

Clean all tools with soap and warm water. Keep container closed when not in use. Store in a cool dry place.

Safety:

See product label and Material Safety Data Sheet for complete safety information. You can request an MSDS sheet by visiting our website at www.dap.com or by calling 888-DAP-TIPS.

Warranty Information:

If you are not satisfied with this product's performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston Street, Suite 200, Baltimore, MD 21224 for product replacement or sales price refund. DAP will not be liable for incidental or consequential damages.