



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® RapidFuse® Fast Curing All Purpose Adhesive Gel

PRODUCT DESCRIPTION

Introducing DAP® RapidFuse® Gel the latest addition to the fast curing all-purpose adhesive technology. Easy to use! Sets in 30 seconds, cures in 30 minutes. Bonds virtually all materials, with a professional-strength bond that is 40% stronger than Polyurethane glues! Plus, unlike traditional super glues, objects can be repositioned within 3 minutes, and the bond won't become brittle resulting in long-lasting durability. The bond is clear – no expanding foam, no dripping glue, no mess. Indoor & outdoor use.



PACKAGING	COLOR	UPC
0.7 oz (20 g) Tube	Clear	7079800178
0.13 oz (4 g) Control Applicator	Clear	7079800179

KEY FEATURES & BENEFITS

- No Drip Gel Formula
- 40% Stronger than Polyurethane Glues
- 2x more durable than Super Glue

PERFORMANCE CHARACTERISTICS

- Bonds Virtually Everything
- Fast Setting - Sets in 30 Seconds
- Cures in 30 minutes
- Repositionable up to 3 minutes
- Interior/Exterior



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

Can be used to repair small home repairs and crafts.

Ideal for Bonding:

- Wood
- Aluminum
- Steel
- Rubber
- ABS
- PVC
- Melamine/Laminate
- Polycarbonate
- Ceramics & Porcelain
- Glass
- Fabric
- Stone & Concrete
- Tile
- Leather
- Paper
- Composites

APPLICATION

Surface Preparation:

Surfaces must be clean, dry, and free of all foreign material. If cleaning is required isopropyl alcohol (rubbing alcohol) is recommended.

Application:

1. Wear gloves to avoid skin contact.
2. For optimal performance, adequately cover one of the two adjoining surfaces.
3. Join the two surfaces and use typical pressure (enough to tightly bring the surfaces together). A large amount of squeeze-out is not necessary.
4. 30 seconds to set, 30 minutes to cure.

If nozzle should clog, simply clear nozzle with a pin or end of paper clip. If required, liquid squeeze-out can be removed with a dry paper towel (do not use water). Cured adhesive must be cut, scraped, or sanded. Avoid direct contact with skin. Do not transfer to any other container. Keep container tightly closed.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Note:

Pretest for glass projects. Bonded items should not be placed in oven, microwave, or dishwasher.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Adhesive Base:	Ethyl Cyanoacrylate
Volatiles:	< 2%
Flash Point:	140 °F – 200 °F (60 °C - 93 °C)
Viscosity:	90,000 – 120,000 cps
Weight/Gal	8.85 lb/gal
Coverage:	5-15 mL/sq. ft. (Optimal coverage is based on substrate evenness and porosity)
Appearance:	Clear Gel
Shelf Life:	18 Months Minimum @ 70°F

CLEAN UP & STORAGE

Prior to cure: Clean excess adhesive with paper towel and replace cap.

After cure: Cured adhesive may be cut, scraped, or sanded away or removed with acetone.

If product comes in contact with skin: soak in warm soapy water and gently peel or roll adhesive off (DO NOT PULL). Flush contact area with water and seek medical attention if needed.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS sheet by calling 888-DAP-TIPS or by visiting our website at dap.com.

WARRANTY

LIMITED WARRANTY: If product fails when used as directed, within one year of purchase, DAP will provide replacement product or refund sales price: call 888-327-8477 with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com