



Technical Bulletin

2400 Boston Street, Suite 200, Baltimore, Maryland 21224
Phone: 410-675-2100 or 800-543-3840

Revised: 8/8/01

DAP® SEAL 'N PEEL™ Removable Weatherstrip Caulk

- Temporary weatherproof seal
- Save energy
- Indoor/outdoor

Packaging: 10.1 fl oz (300ml)
Color: Clear
UPC Number: 18324, 18323

Company Identification:

Manufacturer: DAP Inc., 2400 Boston St., Baltimore, Maryland 21224
Usage Information: DAP HELPLINE: 888-DAP-TIPS, 9:00 am to 7:00 pm EST.
Order Information: 800-327-3339
Fax Number: 410-534-2650
Also, visit the DAP website at www.dap.com.

Product Description:

DAP® SEAL 'N PEEL™ Removable Weatherstrip Caulk is formulated for use as seasonal weather-stripping. Provides a watertight, weatherproof and fast drying seal against air and moisture. Simply apply SEAL 'N PEEL™ to drafty windows and seasonally used doors. Then easily peel it away when spring arrives. Interior and exterior use.

Suggested Uses:

Ideal for use on:

- Window and door frames
- Vents and fans
- Louvers
- Cabinets and closets
- Patio doors
- Air conditioners
- Screen repair

Adheres to:

- Glass
- Plastic
- Ceramics
- Aluminum
- Wood
- Fiberglass
- Drywall
- Concrete
- Metal
- Porcelain
- Vinyl
- Painted surfaces

Surface Preparation & Application:

- Make sure surface is clean, dry and free of loose debris.
- Trim the nozzle to desired bead size, load the cartridge into a caulking gun and puncture inner foil seal.
- Hold the cartridge at a 45° angle and fill the seam with an ample amount of caulk.
- For removal, simply peel away caulk for immediate use of area.

FOR BEST RESULTS

- For best results, do not apply when rain or freezing temperatures are forecasted for 24 hrs. Store away from extreme heat or cold. Do not use for below waterline applications. Do not use on freshly painted surfaces.
- Large gaps or openings may require several layers.
- Product may become more difficult to remove if left on (some surfaces) for more than 1 year.

Physical & Chemical Characteristics:

Tooling Time:	N/A
Tack Free Time:	10 Minutes
Dynamic Joint Movement:	N/A
Life Expectancy:	Temporary
Paintability:	N/A
Odor:	Solvent odor
Consistency:	Smooth, gunnable paste
Polymer:	Synthetic rubber
Volatile:	Aliphatic and aromatic solvents
Flash Point:	45°F (SCC)
Filler:	N/A
Density:	0.88 ± 0.01
Solids:	56.30% ± 1.0% by weight
Weight per Gallon:	7.34 ± 0.05 lbs./gallon
Temperature Service Range:	-30°F to 150°F
Temperature Application Range:	40°F to 100°F
Freeze/Thaw Stability:	Freeze thaw stable
Shelf Life:	12 months minimum @ 70°F
Coverage:	56 linear ft. @ 3/16" diameter bead size or 4 average size windows
MSDS No.:	77136

Clean Up:

While wet use a solvent moistened cloth. After the product has dried, excess material may be easily peeled away.

Safety:

See product label or Material Safety Data Sheet for safety information. You can request an MSDS sheet by calling 888-DAP-TIPS or by visiting our website at www.dap.com.

Warranty Information:

If not satisfied with product performance when used as directed, return used container and sales receipt to DAP Inc., Technical Customer Service, 2400 Boston St., Baltimore, MD, 21224, for product replacement or, sales price refund. DAP will not be liable for incidental or consequential damage.