

DYNAFLEX[®] 920

SUBMITTAL



**ON THE JOB
SINCE 1865.**

JOB REFERENCE	JOB NAME	JOB LOCATION



SUBMITTED TO		SUBMITTED BY	
DATE	PHONE	DATE	PHONE

APPLICATION	PRODUCT SPECIFICATIONS
For use to seal joints around windows, doors, eaves and trim edges.	Meets ASTM C920 – Standard Specification for Elastomeric Sealants

DESCRIPTION	PERFORMANCE FACTS
<p>DAP[®] DYNAFLEX 920 Premium Exterior Elastomeric Sealant is a high performance, permanently flexible sealant developed for professional siding and window installations.</p> <p>It provides a long-lasting seal which helps prevent water and air intrusion.</p>	<p>Amount per Cartridge: 296 mL (10 fl. oz.) Recommended Bead: 1/4" to 3/8" Coverage per Cartridge: 1/4" bead, 30.5 lin. ft. • 3/8" bead, 13.5 lin. ft.</p> <p>Recommended Use: Exterior siding, windows, doors & trim where a durable aesthetic seal is required. Not Recommended For: Interior use; below water line or below grade applications; butt joints less than 1/4" wide or joints exceeding 1/2" wide x 1/2" deep. Features: Adheres to Wet Surfaces • Washout Resistant • Extreme Flexibility • Applies at Temperatures as Low as 20°F • Self Tooling • VOC Compliant • Paintable • Excellent UV Resistance</p> <p>Adheres To: Vinyl • PVC • Aluminum • Metal • Fiber Cement • Masonry • Wood • Most Common Building Materials</p>

BENEFITS	SPECIFICATIONS: ASTM C920 Meets or Exceeds
<p>Caulking where siding meets trim around windows, doors and eaves gives added protection to prevent moisture such as wind-driven rain and snow from penetrating the wall cavity.</p> <p>Caulking also helps reduce condition air loss to increase the energy efficiency of the structure.</p>	<p>PHYSICAL PROPERTIES: VOC Content: CA ARB <4% wt./wt. (NCCS) Solids: 61 ± 0.1 % by weight Application Range: 20°F to 120°F Shelf Life: 18 months Skin Time: 5 minutes Cure Time: 7 to 14 days</p> <p>Uncured Sealant Clean-Up: Mineral Spirits (Do not use to clean skin) Cured Sealant Clean-Up: Cut or Scrape Will Not Freeze</p>