



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® FAST 'N FINAL® Lightweight Spackling

PRODUCT DESCRIPTION

DAP® FAST 'N FINAL® **Lightweight Spackling** lets you patch and prime in one easy step, saving time and money. It dries fast with no need to sand or prime, letting you paint with latex paint in 30 minutes. It is easy to apply with one strike of the putty knife. Won't shrink or crack. Ideal for repairing holes, cracks, and dents in drywall, plaster, wood, and stucco. DAP FAST 'N FINAL Lightweight Spackling is low in odor and for interior or exterior use.



PACKAGING	COLOR	UPC
3 oz.	White	7079812321
½ Pint	White	7079812140
Pint	White	7079812141
Quart	White	7079812142
Gallon	White	7079812143

KEY FEATURES & BENEFITS

- Patch & Prime in One Step
- Fast Drying – 30-Minute Latex Paint Ready
- No Sanding
- Won't Sink or Shrink
- Interior/Exterior use

SUGGESTED USES

Ideal for filling holes, cracks, dents, and defects on: Drywall, Plaster, Wood, Stucco, Brick.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- Do not apply when temperatures are below 40°F.
- Do not use on wear surfaces or where expansion & contraction occur.
- **DO NOT USE AS A SKIM COAT.**
- For exterior/moisture exposed applications, first apply waterproof primer, then apply waterproof coating or paint prior to moisture exposure. Do not use for tuck pointing applications on brick.

APPLICATION

1. Surface must be free of grease, oil, and other foreign matter.
2. Stir thoroughly before use.
(When using the 2.8 oz tube, remove top, grip tube bottom & twist up a very small amount (about 1/16") of filler. Either apply directly to surface or using built-in spackling knife, scrape off spackling from top of tube & apply to wall)
3. Using a clean putty knife, press spackling into hole or crack.
4. Draw blade firmly across the surface to remove excess material in one strike.
5. For a smoother finish, dip putty knife into water and lightly smooth spackling.
6. One application is usually sufficient for small repairs.
For repairs deeper than 1/8", apply two or more layers allowing spackling to dry between applications.
7. May be painted within 30 minutes with a latex paint. Please follow paint manufacturer's instructions for application.
8. If sanding is desired, or if an oil-based paint is to be used, allow to dry thoroughly (approximately 24 hours).



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Thick Paste
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Paint	Takes either oil or latex-based paint
Solids	75% by volume (or 42% by weight)
Application Temperature	40°F or higher
Service Temperature	-20°F to 150°F
Shelf Life	12 months
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	30 minutes depending on temperature, humidity, and depth of fill

CLEAN UP & STORAGE

Wash tools immediately after use with water. Dried material must be removed by scraping or sanding. Be sure container lid/cap is closed and tightly sealed and store in a cool, dry place, away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform when used as directed within one year of date of purchase, call 888-DAP-TIPS with your sales receipt and product container available for replacement product or sales price refund. DAP Global Inc. will not be responsible for incidental or consequential damages.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224 **Usage**

Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert" **Order**

Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com