



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® PLASTIC WOOD-X™ ALL PURPOSE WOOD FILLER with DryDex® Dry Time Indicator

PRODUCT DESCRIPTION

DAP® PLASTIC WOOD-X™ All Purpose Wood Filler with DryDex® Dry Time Indicator goes on pink and dries natural for an invisible repair. It is a high quality, latex-based wood filler formulated to create a surface and body that looks and acts like real wood. It can be used to repair cracks, gouges, holes and other surface defects on furniture, woodwork, molding, cabinets, paneling, plywood, windows, doors and painted surfaces. This easy-to-use filler is low in odor and cleans up with water. The thick, knife-grade formula can be molded and sculpted making it ideal for corners, vertical and unsupported surfaces. It offers easy handling by spreading smoothly and evenly. When dry, DAP PLASTIC WOOD-X All Purpose Wood Filler can be sanded, cut, planed, drilled, nailed or screwed, stained and painted. It is shrink, crack and crumble resistant and provides strong nail and screw anchoring. Interior/exterior use.



| PACKAGING | COLOR | UPC |
|-----------|---------|------------|
| 5.5 oz | Natural | 7079800540 |
| 8 oz | Natural | 7079800541 |
| 16 oz | Natural | 7079800542 |
| 32 oz | Natural | 7079800543 |
| Kit | Natural | 7079800596 |

KEY FEATURES & BENEFITS

- Goes on PINK and dries NATURAL
- Easy-to-use, latex-based formula
- Water clean-up & low odor
- Looks and acts like real wood
- Can be sanded, planed, cut, drilled, screwed & nailed
- Shrink, crack and crumble resistant
- Thick, knife-grade formula can be molded & sculpted
- Ideal for corners and vertical surfaces
- Stainable & paintable
- Strong nail & screw anchoring
- Interior/Exterior use



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

For filling nail holes, gouges, cracks, scratches & imperfections on furniture, woodwork, molding, cabinets, paneling, plywood, windows, doors and painted surfaces.

APPLICATION

1. Surface must be clean, dry, structurally sound and free of all foreign material. De-gloss surface if necessary for best adhesion.
2. Surface, wood filler and air temperature should be above 40°F.
3. If staining, test wood filler with desired stain on scrap wood before filling to ensure desired stain color.
4. Stir product with putty knife before application.
5. Apply wood filler into area to be filled. Press firmly into place using a putty knife or tool.
6. Avoid overspreading filler on surrounding surfaces. Overfill slightly to allow for sanding and settling. Most repairs require just one fill. Larger and deeper holes may require more than one application.
7. For larger and deeper holes, apply thin layers to build up thick sections. Allow wood filler to dry before applying next layer.
8. Allow to dry thoroughly before sanding: approximately 2 to 6 hours for shallow fills up to 1/8" and 36 hours for deeper fills 1/4" and over. Sand with medium sandpaper.
9. May be painted with latex-based paint immediately after sanding, or after 12 hours if using an oil-based paint.
10. Exterior applications and applications subject to water exposure must be sealed with a waterproof coating prior to moisture exposure.
11. Reseal container tightly with lid.
12. Keep from freezing.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

| | |
|-------------------------|-----------------------------------------------------------------------------------------------------------------------------|
| Consistency | Stiff Paste |
| Vehicle | Latex Polymer |
| Filler | Inert Pigment |
| Volatile | Water |
| Solids | 80% by weight |
| Odor | Mild |
| Shelf Life | 12 Months |
| Application Temperature | 40°F to 100°F |
| Dry Time | Depending on temperature and humidity: 2 to 6 hours in shallow fills up to 1/8"; up to 36 hours in deep fills 1/4" and over |

CLEAN UP & STORAGE

Wipe off excess filler from surface and tools with a damp cloth before material dries. Dried wood filler must be sanded or scraped away. Reseal tightly with lid after each use. Store in a cool, dry place away from extreme heat or cold

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

Limited One-Year Warranty:

DAP Global Inc. warrants to the original purchaser for a period of one year that its product will perform to DAP published written product specifications, if used as directed. If the product fails to perform, call 888-DAP-TIPS and return the product and container with your sales receipt for either replacement product or a refund of the sales price, at DAP's sole discretion. Any implied warranties, including the implied warranty of merchantability and fitness for a particular purpose, are expressly limited to the duration of this limited written warranty. **Incidental and consequential damages are expressly disclaimed and DAP's maximum liability is limited to the amount of the original purchase price of the DAP product.**

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland
21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com