



TECHNICAL DATA SHEET


2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Liquid Cement Crack Filler

PRODUCT DESCRIPTION

DAP® Liquid Cement Crack Filler is an easy-to-use, ready mixed product for the repair of horizontal concrete cracks. Repairs are ready for light foot traffic 30-45 minutes following application when directions are properly followed. Liquid Cement is self-leveling and dries gray to match most existing concrete.

NOTE: Fills cracks up to ½" in width. For cracks greater than ½" in width, use DAP Ready-Mixed or Dry Mix Concrete Patch.



PACKAGING	COLOR	UPC
Quart	Light Grey	0 70798 37584 0

KEY FEATURES & BENEFITS

- Repairs cracks and surface defects in concrete
- Self-leveling
- Easy to use, ready-mixed formula

SUGGESTED USES

It is ideal for filling and repairing concrete and cement cracks, including sidewalks, driveways, steps, patios and basements.

APPLICATION

Surface Preparation

1. Surface must be structurally sound and free of all foreign material.
2. If the crack is deeper than ¼" (6 mm), use backer rod or sand to fill the crack to within ¼" (6 mm) of the surface.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

3. Deep cracks may require more than one application due to shrinkage while drying and will have extended drying times.

Application

1. Gently shake Liquid Cement bottle prior to opening and before each use to ensure consistent mixture.
2. Bottle nozzle should be snipped with scissors to initially open to make a 1/4" (6 mm) to 3/8" (9 mm) opening.
3. Fill crack in 1/4 inch layers allowing at least 24 hours between applications.
4. For very thin cracks, Liquid Cement may be "pressed" or troweled flat into and around crack.

For Best Results

1. Do not apply in cracks wider than 1/2" (12 mm).
2. Apply Between: 45°F - 100°F
3. Do not apply if rain is expected within 24 hours.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Appearance/Consistency	Smooth, Pourable Liquid
Color	Gray
Flash Point	>212°F (>100°C)
Fully Dried**	24 hours
Shelf Life	12 months
Application Temperature Range	45°F to 100°F
Coverage	One quart (946 mL) bottle will fill a 1/4" x 1/2" (6 x 12 mm) crack 35' (11.6M) long.

*** Depending on temperature, humidity and depth of repair.*

CLEAN UP & STORAGE

Clean up excess wet material with a damp sponge before it sets. Excess dried cured material must be mechanically cut, scraped, chipped, or ground away. Clean skin and tools with warm water and soap. Store container in a cool, dry place away from extreme heat or cold. Protect from freezing.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

WARRANTY

LIMITED ONE-YEAR WARRANTY: DAP Global Inc. warrants to the original purchaser for a period of one year from the date of purchase that its product will perform to DAP published written product specifications, if used as directed. If the product fails to perform, call 888-DAP-TIPS and return the product and container with your sales receipt for either replacement product or a refund of the sales price, at DAP's sole discretion. Any implied warranties, including the implied warranty of merchantability and fitness for a particular purpose, are expressly limited to the duration of this limited written warranty. **Incidental and consequential damages are expressly disclaimed and DAP's maximum liability is limited to the amount of the original purchase price of the DAP product.**

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com