



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Flexible Floor Patch and Leveler

PRODUCT DESCRIPTION

DAP® Flexible Floor Patch and Leveler is a ready-to-use latex-based product used to fill cracks, fasteners or knotholes, and level low areas in plywood subfloors or concrete surfaces. The Floor Patch and Leveler will remain flexible, allowing the plywood subfloor to flex without cracking the filled-in areas.



PACKAGING	COLOR	UPC
Quart	Light Grey	7079859184
Gallon	Light Grey	7079859190

KEY FEATURES & BENEFITS

- For plywood subfloors and concrete
- Crack Resistant Formula Can be sanded to a feathered edge

SUGGESTED USES

It is ideal for filling and leveling surfaces prior to the installation of carpeting, vinyl floor tile, and more.

APPLICATION

1. Surface must be clean, dry, structurally sound and free of all foreign material.
2. Using a broad knife or a smooth face trowel, apply the Floor Patch and Leveler directly to the area to be filled.
3. Apply up to ¼ inch and let dry approximately 6 hours to a hard finish (longer in cooler & humid conditions. For thickness greater than ¼ inch, apply in multiple coats allowing each coat to dry completely between applications.
4. Feather edge all applications to ensure a smooth surface. Product can not be sanded smooth.
5. Maximum application depth is ¾ of an inch.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

6. Test for dryness by pressing a coin to patch. No indentation typically indicates sufficient dry time for floor covering application. Dry time will increase with thickness of patch, lower temperature and/or higher moisture.

NOTE: DAP® Flexible Floor Patch and Leveler is not intended to be traffic surface, likewise, paint application is not recommended to create a traffic surface.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Paste
Flash Point	>212°F (>100°C)
Application Temperature	40°F to 90°F
Service Temperature	-20°F to 120°F
Shelf Life	12 months
Dry Time**	6 hours
Coverage	One-quart fills 1 to 2 square feet ¼ inch thick.

** Depending on temperature, humidity and depth of repair.

CLEAN UP & STORAGE

Clean up excess wet material with a damp sponge before it sets. Excess dried material must be mechanically cut, scraped, chipped, or ground away. Clean skin and tools with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

LIMITED ONE-YEAR WARRANTY: DAP Global Inc. warrants to the original purchaser for a period of one year from the date of purchase that its product will perform to DAP published written product specifications, if used as directed. If the product fails to perform, call 888-DAP-TIPS and return the product and container with your sales receipt for either replacement product or a refund of the sales price, at DAP's sole discretion. Any implied warranties, including the implied warranty of merchantability and fitness for a particular purpose, are expressly limited to the duration of this limited written warranty. **Incidental and consequential damages are expressly disclaimed and DAP's maximum liability is limited to the amount of the original purchase price of the DAP product.**



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com