



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® All-Purpose Stucco Patch (Dry Mix)

PRODUCT DESCRIPTION

DAP® All-Purpose Stucco Patch may be used to repair large holes and cracks in interior and exterior stucco surfaces. It's easy to mix formula blends naturally with existing stucco for a professional finish. Durable and permanent. Easy to tool and paint. Interior/exterior use.



PACKAGING	COLOR	UPC
25 lb. bag	White	7079810502

KEY FEATURES & BENEFITS

- Professional quality, for repairs in stucco surfaces
- Easy to tool and paint
- Durable
- Interior/Exterior use

SUGGESTED USES

Ideal for filling holes, cracks, dents and defects on stucco

APPLICATION

1. Surface must be clean, dry, structurally sound and free of all foreign material.
2. Add stucco patch to clear water in clean container mixing 4 parts of powder to 1 part of water by volume.
3. Let the mixture set for 15 minutes to thicken then re-stir until smooth. Do not mix more material than can be used in 1 to 2 hours. Discard any material that has begun to cure.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

4. Apply stucco patch with a clean putty knife or trowel. For fills over 1/4" deep apply 2 or more layers allowing each layer to dry before applying the next layer. Use a rubber float to blend patch with the existing stucco surface.

NOTE: Consult paint manufacturer's recommendations before decorating.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Application Temperature Range	50°F to 90°F
Working Time*	1 to 2 hours
Setting Time*	2 to 4 hours
Final Cure	3 days
Mixing Ratio	4:1 by volume (small batch). Full bag mixing instructions: Add 5 pt. water to 25 lb. bag Stucco Patch
Full bag Coverage	10-12 sq. ft. with 1/4" thickness

** Depending on temperature, humidity and depth of repair.

CLEAN UP & STORAGE

Clean up excess uncured material with a damp sponge before it sets. Excess cured material must be mechanically cut, scraped, chipped, or ground away. Clean skin and tools with warm water and soap. Store the remaining powder in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

LIMITED WARRANTY

LIMITED ONE-YEAR WARRANTY: DAP Global Inc. warrants to the original purchaser for a period of one year from the date of purchase that its product will perform to DAP published written product specifications, if used as directed. If the product fails to perform, call 888-DAP-TIPS and return the product and container with your sales receipt for either replacement product or a refund of the sales price, at DAP's sole discretion. Any implied warranties, including the implied warranty of merchantability and fitness for a particular purpose, are expressly limited to the duration of this limited written warranty. **Incidental and consequential damages are expressly disclaimed and DAP's maximum liability is limited to the amount of the original purchase price of the DAP product.**

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com