



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® All Purpose Stucco Patch (Ready Mix)

PRODUCT DESCRIPTION

DAP® All-Purpose Stucco Patch may be used to repair small holes and cracks in interior and exterior stucco surfaces. It's ready to use sanded formula blends naturally with existing stucco for a professional finish.



PACKAGING	COLOR	UPC
Quart	White	7079810504
Gallon	White	7079860590

KEY FEATURES & BENEFITS

- For repairing small holes and cracks in stucco surfaces
- Durable and permanent
- Textured finish
- Ready to use
- Easy to tool and paint
- Interior/exterior use

SUGGESTED USES

For patching small holes and cracks in stucco surfaces.

FOR BEST RESULTS

- To repair large breaks, cracks and holes in stucco surfaces, use DAP Stucco Patch Dry Mix.
- **DO NOT USE AS A SKIM COAT.**



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

APPLICATION

1. Surface must be clean, dry and free of loose paint, plaster, wax, dust and dirt.
2. Apply stucco patch with a clean putty knife or trowel. For fills over 1/4" deep, apply 2 or more layers allowing each layer to dry before applying the next one.
3. Use a rubber float to blend patch with the existing stucco surface.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Flash Point:	>212°F (>100°C)
Setting Time:**	2 to 4 hours
Final Cure:**	3 days
Odor:	Mild
Consistency:	Coarse, thick paste
Vehicle:	Latex emulsion
Volatile:	Water
Filler:	Calcium carbonate, sand
Solids:	84 ± 1.0% by weight
Weight per Gallon:	15.6 lbs./gal.
Shelf Life:	12 months
Coverage:	1 qt./946 mL 12-18 sq. ft.
	1 gal. 48-72 sq. ft. NOTE: These figures are approximate and may vary with job site conditions

** Depending on temperature, humidity and depth of repair.

CLEAN UP & STORAGE

Clean up excess wet material with a damp sponge before it sets. Excess dried cured material must be mechanically cut, scraped, chipped, or ground away. Clean skin and tools with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

LIMITED WARRANTY

LIMITED ONE-YEAR WARRANTY: DAP Global Inc. warrants to the original purchaser for a period of one year from the date of purchase that its product will perform to DAP published written product specifications, if used as directed. If the product fails to perform, call 888-DAP-TIPS and return the product and container with your sales receipt for either replacement product or a refund of the sales price, at DAP's sole discretion. Any implied warranties, including the implied warranty of merchantability and fitness for a particular purpose, are expressly limited to the duration of this limited written warranty. **Incidental and consequential damages are expressly disclaimed and DAP's maximum liability is limited to the amount of the original purchase price of the DAP product.**

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com