



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® 2in1 Wall & Ceiling Spray Texture: Popcorn Water Based

### PRODUCT DESCRIPTION

**DAP® 2in1 Wall & Ceiling Spray Texture Popcorn Water Based** is a pro-grade solution featuring a powerful, adjustable nozzle. Simply aim up or down to switch between wall and ceiling applications. With a quick 30-minute dry time, our clog-resistant, fast-drying formula is designed for efficiency and does not require priming. Its ergonomic system provides professional hopper results with a high-pressure flow, delivering a wide, even spray for a truly seamless blend to existing textured surfaces. Engineered for versatility, precision, and speed, this is the ultimate tool to get the job done right.



| PACKAGING | COLOR | UPC        |
|-----------|-------|------------|
| 20 oz can | White | 7079850025 |

### KEY FEATURES & BENEFITS

- Ideal for vertical, overhead and hard to reach areas
- Wide coverage with even spray application
- Excellent match to textured surfaces
- 30-minute paint ready time depending on temperature, humidity & application thickness
- Strong and durable cure
- Low odor
- Easy water clean-up

### SUGGESTED USES

#### USE FOR REPAIRING TEXTURED SURFACES:

- Drywall
- Stucco
- Plaster



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## APPLICATION



Product can be messy. **Protect work area with drop cloths.** Ensure surface is clean, dry, structurally sound and free of all foreign material. Make any necessary repairs to surface and ensure it is smooth and dry prior to applying spray texture. **IMPORTANT:** be sure that the area is well ventilated and proper safety gear is worn.




**SHAKE** can upside down **vigorously** for more than one minute after hearing mixing marble moving freely in the can. Frequently shake upside down between sprays. Product will not work as intended if this step is skipped.



**UNLOCK** tab by bending backwards. THE SAFETY TAB IS DESIGNED TO RE-LOCK, DO NOT BREAK OFF.



**AIM** nozzle upward to desired spray angle, nozzle can rotate up to 60 degrees. **BE SURE TO POINT AWAY FROM FACE AND PEOPLE.**



**ENGAGE** pressure by spraying into a trash can & **TEST** a quick burst on scrap materials to activate before applying to work surface.



**SPRAY** holding can approximately 12"-18" away from surface using intermittent bursts, sweeping across the repair in a quick, continuous motion. **IMPORTANT:** keep tip/nozzle clean while spraying by wiping with damp cloth. For superior blending, feather the repair texture into surrounding area. Add coverage as needed to match the existing texture density. If not satisfied, scrape off and reapply.



**PAINT:** Allow texture to dry for 30 minutes prior to painting. Dry time may be longer in cooler/humid conditions or with thicker applications. Follow paint manufacturer's instructions for best results. For exterior/moisture exposed applications, apply a waterproof coating prior to moisture exposure.



**CLEAN-UP:** Wet texture can be cleaned up with water. Dry texture must be cut, scraped or sanded away. Place nozzle in the upright position, invert can by pointing straight down. Spray onto a disposable surface until no texture sprays out. Be sure to remove any texture build up from tip/nozzle to prevent material drying on tip/nozzle. **STORE:** adjust spray angle to starting position and re-lock using tab. Store in cool, dry conditions.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## FOR BEST RESULTS

- **IMPORTANT: Shake vigorously** before attempting to spray, and frequently during application
- Protect work area with drop cloths
- Dispense a quick burst on scrap material to activate
- Apply in temperatures between 65°F - 80°F
- Spray using intermittent bursts
- Practice applying on scrap material before use
- Store away from direct heat in temperatures ranging from 40°F to 90°F

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

|                                             |                         |
|---------------------------------------------|-------------------------|
| Appearance/Consistency                      | White textured material |
| Base Polymer                                | Acrylic Latex           |
| Weight % Solids                             | 46                      |
| Density (lbs per gallon)                    | 10.25                   |
| Odor                                        | Low odor                |
| Clean Up                                    | Water                   |
| Shelf Life                                  | 12 months               |
| Coverage                                    | 12 sq. ft.              |
|                                             |                         |
| <b>Typical Application Properties</b>       |                         |
| Application Temperature Range               | 65°F - 80°F             |
|                                             |                         |
| <b>Typical Cured Performance Properties</b> |                         |
| Service Temperature Range                   | 40° F - 90°F            |

## CLEAN UP & STORAGE

Clean-up wet texture with water. Dry texture must be cut, scraped or sanded away. Store in cool, dry conditions.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling **888-DAP-TIPS**.

## WARRANTY

**LIMITED ONE-YEAR WARRANTY:** Warranty terms available at [dap.com/warranty](http://dap.com/warranty). For a free written copy, call (888)-DAP-TIPS.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Global Inc., 2400 Boston Street, Suite 200, Baltimore, Maryland 21224

**Usage Information:** Call 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on “Ask the Expert”

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**