



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® KWIK SEAL® Adhesive Caulk - Clear

### PRODUCT DESCRIPTION

DAP® KWIK SEAL® KITCHEN & BATH ADHESIVE CAULK is an easy-to-use acrylic latex that bonds like a glue and seals like a caulk. Once cured, it is mold and mildew resistant and 100% waterproof. It is easy to apply, paintable, low in odor and water clean-up. Interior use.



PACKAGING	COLOR	UPC
10.1 fl oz (300 mL) Cartridge	Clear	7079818008
5.5 fl oz (162 mL) Tube	Clear	7079818242

### KEY FEATURES & BENEFITS

- Cured caulk is mold & mildew resistant
- 100% waterproof seal
- Bonds like glue, seals like a caulk
- Paintable
- Easy water clean-up & low odor
- VOC compliant
- Interior use

### SUGGESTED USES

#### USE FOR CAULKING & SEALING:

- Tubs
- Showers
- Sinks
- Backsplashes
- Vanities
- Countertops
- Fixtures
- Sealing around pipes
- Repairing loose tiles



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## ADHERES TO:

- Wood – painted & unpainted
- Ceramic
- Porcelain
- Glass
- Most metals
- Most plastics
- Drywall
- Plaster
- Brick
- Stone
- Most common building materials

## FOR BEST RESULTS

- Apply in temperatures above 40°F.
- Not for continuous underwater use, high temperature surfaces or surface defects.
- Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8", use backer rod material.
- **Caulk applies white and dries clear in 7-14 days depending on joint depth, temperature and humidity.**
- Wait 36 hours before exposing to water.
- Store caulk away from extreme heat or cold.

## APPLICATION

### Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material. Rubbing alcohol (Isopropyl alcohol) is recommended for removing soap film and soil.

### Product Application

1. If using the squeeze tube, remove cap, and cut nozzle at 45° angle to desired bead size.
2. If using the cartridge, cut nozzle at 45° angle to desired bead size, puncture inner foil seal, load into caulk gun.
3. Fill gap or joint with caulk.
4. If necessary, tool or smooth the bead of caulk with a finishing tool before caulk skins over.
5. Clean up excess wet caulk with a damp sponge before it skins over. Excess dried caulk must be cut or scraped away. Clean hands and tools with warm water and soap.
6. **Allow caulk to dry clear (approximately 7-14 days) before painting with latex or oil-based paints.**
7. **Wait 36 hours before exposing to water.**
8. Reseal container for storage and reuse.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

<b>Typical Uncured Physical Properties</b>	
Appearance/Consistency	Gunnable, non-sag paste
Base Polymer	Siliconized acrylic polymer
Filler	Not applicable
Volatile	Water
Weight % Solids	53%
Density (lbs per gallon)	8.5
Odor	Very mild
Clean Up	Water
Flash Point	>212°F (100°F)
Freeze Thaw Stability (ASTM C1183)	Passes 5 cycles
Shelf Life	12 months
Coverage	10.1 fl oz: 55 linear feet at a 3/16" diameter bead 5.5 fl oz: 30 linear feet at 3/16" diameter bead
<b>Typical Application Properties</b>	
Application Temperature Range	40°F to 100°F
Tooling Time (Working Time)	60 minutes
Tack Free Time	60 minutes
Return to Service Time	36 hours
Full Dry Through	7-14 days
Vertical Sag (ASTM D2202)	0.05"
<b>Typical Cured Performance Properties</b>	
Service Temperature Range	-20°F to 180°F
Water Ready Time	36 hours
Paint Ready Time	7-14 days (when sealant turns clear)
Mildew Resistance	Cured caulk is mold & mildew resistant



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## CLEAN UP & STORAGE

Clean up excess wet caulk with a damp sponge before it skins over. Excess dried caulk must be cut or scraped away. Clean hands and tools with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS by visiting our website at [dap.com](http://dap.com) or calling 888-DAP-TIPS.

## WARRANTY

LIMITED ONE-YEAR WARRANTY: Warranty terms available at [dap.com/warranty](http://dap.com/warranty). For a free written copy, call (888)-DAP-TIPS.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call 888-DAP-TIPS or visit [dap.com](http://dap.com) & click on “Ask the Expert”

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**