



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® KWIK SEAL PLUS® Premium Kitchen & Bath Adhesive Sealant – Clear

PRODUCT DESCRIPTION

DAP® KWIK SEAL PLUS® Premium Sealant contains **MoldGuard Technology** Antimicrobial Product Protection to fight the growth of stain and odor-causing bacteria, mold and mildew on the sealant. The sealant is easier to clean and stays cleaner between cleanings. KWIK SEAL PLUS® siliconized acrylic latex sealant provides strong adhesion and excellent flexibility for 100% waterproof and crackproof seal around tubs, sinks, showers, countertops, backsplashes and fixtures. It is easy to apply, paintable, low in odor and water clean-up. Interior use.



PACKAGING	COLOR	UPC
10.1 fl oz (300 mL) Cartridge	Clear	7079818516
5.5 fl oz (162 mL) Tube	Clear	7079818546

KEY FEATURES & BENEFITS

- **MoldGuard Technology** fights the growth of stain & odor-causing bacteria, mold & mildew on the sealant
- 100% waterproof seal
- Crack resistant
- Paintable
- Easy water clean-up
- Low odor
- VOC compliant
- Interior use



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

USE FOR CAULKING & SEALING:

- Tubs
- Showers
- Sinks
- Backsplashes
- Vanities
- Countertops
- Fixtures
- Sealing around pipes
- Repairing loose tiles

ADHERES TO:

- Wood – painted & unpainted
- Ceramic
- Porcelain
- Glass
- Most metals
- Most plastics
- Fiberglass
- Drywall
- Plaster
- Granite
- Cultured marble
- Brick
- Stone
- Most common building materials

FOR BEST RESULTS

- Apply in temperatures above 40°F.
- Not for continuous underwater use, high temperature surfaces or surface defects.
- Joint size should not exceed 3/8" wide x 3/8" deep. If joint depth exceeds 3/8", use backer rod material.
- **Sealant applies white and dries clear in 7-14 days depending on joint depth, temperature and humidity.**
- **Wait 18 hours before exposing to water.**
- Store caulk away from extreme heat or cold.

APPLICATION

Surface Preparation

Surface must be clean, dry, structurally sound and free of all foreign material. Rubbing alcohol (Isopropyl alcohol) is recommended for removing soap film and soil.

Product Application

1. If using the squeeze tube, remove cap, and cut nozzle at 45° angle to desired bead size.
2. If using the cartridge, cut nozzle at 45° angle to desired bead size, puncture inner foil seal, load into caulk gun.
3. If necessary, tool or smooth the bead of caulk with a finishing tool before caulk skins over.
4. Clean up excess wet caulk with a damp sponge before it skins over. Excess dried caulk must be cut or scraped away. Clean hands and tools with warm water and soap.
5. **Allow caulk to dry clear (approximately 7-14 days) before painting with latex or oil-based paints.**



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

6. **Wait 18 hours before exposing to water.**
7. Reseal container for storage and reuse.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Gunnable, non-sag paste
Base Polymer	Acrylic copolymer
Filler	Not applicable
Volatile	Water
Weight % Solids	61%
Density (lbs per gallon)	8.7
Odor	Very mild
Clean Up	Water
Flash Point	>212°F (100°C)
Freeze Thaw Stability (ASTM C1183)	Passes 5 Cycles
Shelf Life	12 months
Coverage	10.1 fl oz: 55 linear feet at a 3/16" diameter bead 5.5 fl oz: 30 linear feet at 3/16" diameter bead
Typical Application Properties	
Application Temperature Range	40°F to 120°F
Tooling Time (Working Time)	15 minutes
Tack Free Time	30 minutes
Return to Service Time	18 hours
Full Dry Through	7-14 days
Vertical Sag (ASTM D2202)	0.05"
Typical Cured Performance Properties	
Service Temperature Range	-20°F to 150°F
Water Ready Time	18 hours
Paint Ready Time	7-14 days (when sealant dries clear)
Mildew Resistance	MoldGuard Technology fights the growth of stain & odor-causing bacteria, mold & mildew on the sealant

CLEAN UP & STORAGE



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Clean up excess wet caulk with a damp sponge before it skins over. Excess dried caulk must be cut or scraped away. Clean hands and tools with warm water and soap. Store container in a cool, dry place away from extreme heat or cold.

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request a SDS by visiting our website at dap.com or calling 888-DAP-TIPS.

WARRANTY

LIMITED ONE-YEAR WARRANTY: Warranty terms available at dap.com/warranty. For a free written copy, call (888)-DAP-TIPS.

COMPANY IDENTIFICATION

Manufacturer: DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on “Ask the Expert”

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com