



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® DAPTEX® Plus Multi-Purpose Latex Insulating Foam Sealant

PRODUCT DESCRIPTION

DAPtex® Plus Insulating Foam Sealant is a latex-based formula that seals out drafts, reduces energy loss and prevents pest infiltration. It is a great choice for sealing around windows and doors during installation because DAPtex® Plus will not over expand like many polyurethane foams. The reusable, non-clogging applicator and easy soap and water clean-up eliminates the waste and mess of other insulating foam sealants. DAPtex® Plus can be tooled, molded and painted, making it ideal for patch and repair projects, such as holes or gaps in walls, trim and molding. The dried foam remains flexible, minimizing the need to trim excess application.



PACKAGING	Case	COLOR	UPC
12 oz (340g) Can	12	White	7079818836

KEY FEATURES & BENEFITS

- Seals, Insulates, Weatherproofs
- Improved Durability, Flexibility and Water Resistance



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

- Low Pressure Formula - Safe for all Windows & Doors – Meets AAMA 812
- Reusable Non-Clogging Applicator
- Easy Water Clean-Up
- Bright White Foam

SUGGESTED USES

- Window and door frames / jambs
- Sealing and insulating around pipes, ducts, vents Through-penetrations
- Filling small gaps and voids around above-grade foundations and crawl spaces.
- Perimeter sealing of electrical switch and outlet boxes. NOTE: Not for use inside of electrical switch and outlet boxes.
- DAPtex® Plus provides an insulating seal to wood, concrete, brick, vinyl, steel and aluminum.

FOR BEST RESULTS

- Apply in temperatures between 45°F- 95°F
- Surface must be clean, dry, and free of all foreign material
- Apply in spaces with 50% relative humidity or less
- If used outdoors, paint after full cure
- Use around, not inside, electrical switch and outlet boxes

APPLICATION

DIRECTIONS: Important – read all directions and cautions before use. Always wear eye protection, work clothes and use in well-ventilated areas. Use drop cloths. Product is flammable during dispensing – turn off sources of ignition prior to use.

Preparation: Surface must clean, dry, and free of all foreign material. Shake can vigorously for 1 minute before use. Push straw into nozzle located above the trigger. Remove safety tab above trigger. Important: Before starting the job, first practice dispensing onto scrap materials.

Application: Slowly dispense foam from can in upright position, filling cavity to 90% to allow for minimal expansion. For best results, tool or shape while wet. Do not trim or remove skin of the cured foam. On exterior applications, apply a quality exterior latex paint to foam after full cure. If storing for reuse, remove straw and clean it and nozzle with warm water. Cured material can be removed from nozzle or straw with a pipe cleaner or paper clip. Not recommended for use at or below grade, or for closed cavities. For gaps more than 2" deep, use multiple layers of 1" each.

Clean-up: Uncured foam can be cleaned up with soap and water. Excess cured sealant can be scraped off.

Storage/Re-Use: If storing for reuse, remove straw and clean it and nozzle with warm water. Cured material can be removed from nozzle or straw with a pipe cleaner or paper clip.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Yield per can (1/4" bead)	400 linear feet
Dry Time/ tack free	10 minutes
Dry Time (typical indoor conditions - ~68 °F / <50% RH))	24 hours
Shelf Life	18 months (unopened)
Application Temperature Range	45°F to 95°F (16°C ~ 38°C)
Color	Bright White
Consistency	Foam (sponge-like consistency when cured)
Chemistry	Latex

SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or calling 888-DAP-TIPS.

WARRANTY

LIMITED ONE- YEAR WARRANTY: Warranty terms available at dap.com/warrant. For a free written copy, call 888-DAP-TIPS

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call 888-DAP-TIPS or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com