



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® FAST DRY High Strength Spackling with DRYDEX® Technology

### PRODUCT DESCRIPTION

**DAP® FAST DRY High Strength Spackling with DryDex® technology** is a professional-grade spackling designed for durability, speed, and ease of use. It features a unique dry time indicator—with DRYDEX® technology\*—that clearly shows when the surface is dry and ready for sanding or painting, helping to eliminate guesswork and reduce errors.

This ready-to-use formula goes on smoothly and resists sinking, shrinking, or cracking. Many repairs can be painted in as little as 15 minutes, making it ideal for fast-paced projects. Typically requiring just one coat, it dries hard, sands easily, and delivers a professional finish every time.



PACKAGING	COLOR	UPC
16 fl. oz. (473 mL)	Pink to White	7079818450
32 fl. oz (846 mL)	Pink to White	7079818451

### KEY FEATURES & BENEFITS

- Ideal for large drywall repairs
- From America's #1 Seller of Spackling\*
- Dry Time Indicator – Goes on Pink Dries White
- Finish Fast - 15-minute paint ready on repairs 1" x 1/8" in depth or smaller, depending on temperature and humidity
- 1 Coat Application for repairs 1" wide by 1/8" in depth – Won't sink or shrink
- No priming required – Won't flash paint
- Reduces errors
- Easy-to-use, latex-based formula
- Easy water clean-up & low odor
- Interior/Exterior use

\* Of spackling based on US home improvement market dollar sales in the spackling category



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## SUGGESTED USES

Ideal for filling holes, cracks, dents, defects and larger repairs in drywall and plaster.

## FOR BEST RESULTS

If spackling seems dry when opening, stir completely and evenly until it's a smooth, creamy consistency.

Do not apply when temperatures are below 40°F.

Do not apply outside if rain is expected within 24 hours.

### DO NOT USE AS A SKIM COAT.

For exterior applications, always topcoat with high quality exterior-grade paint before moisture contact.

## APPLICATION

### APPLICATION:

1. Surface must be clean, dry, structurally sound, and free of all foreign material. De-gloss surface, if necessary, for better adhesion to drywall surface.
2. If spackling seems dry when opening, stir completely and evenly until it's a smooth, creamy consistency.
3. Apply with a clean putty knife.
4. For a smooth finish, dip putty knife in water and lightly smooth spackling.
5. One application is usually sufficient for repairs 1" wide x 1/8" in depth.
6. May be painted in as little as 15 minutes with latex paint on repairs 1" x 1/8" in depth or smaller, depending on temp., humidity and depth of fill. If sanding, additional dry time may be needed, approximately 60 minutes for repairs 1" x 1/8" in depth or smaller. If sanding is required, use medium-grit sandpaper and finish with fine-grit for a smooth finish. Wet sanding is recommended to avoid generation of dust.
7. Spackling will change color to white when surface can accept a second application or is ready to be sanded or painted in approximately 15 min to 1 hour (depending on temperature, humidity and depth of fill).
8. Paint with latex or oil-based paints. Ensure that DAP® FAST DRY High Strength Spackling is thoroughly dry before applying oil-based paint.
9. Clean tools immediately with water. Dry material must be cut or scraped away.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency	Thick paste, contents may appear dry when opening.
Vehicle	Latex Polymer
Volatile	Water
Filler	Inert Filler
Odor	Mild
Weight/Gallon	5.01-5.11 lbs./gal
Solids	63%
Application Temperature	Between 40°F -100°
Service Temperature	0°F to 150°F
Shelf Life	12 months
Flash Point	100°C
Freezing	Freeze/thaw stable 5 cycles at 0°F
Dry Time	15 min time to paint (1" x 1/8" depth, depending on temperature, humidity)

## CLEAN UP & STORAGE

Clean tools immediately with water. Dry Material must be cut or scrapped away. Be sure container is closed and tightly sealed. Store container in a cool, dry place away from extreme heat or cold.

## SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or by calling 888-DAP-TIPS.



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## LIMITED ONE-YEAR WARRANTY

Warranty terms available at [dap.com/warranty](http://dap.com/warranty). For a free written copy, call 888-DAP-TIPS.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Global Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call **888-DAP-TIPS** or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**