

IMPORTANT: Provide this information to employees, customers, and users of this product. Read this SDS before handling or disposing of this product. This product is covered by the OSHA Hazard Communication Standard and this document has been prepared in accordance with requirements of this standard. All abbreviated terms used in this SDS are further described in Section 16.

1. Identification

Product Name:	Silicone Plus Premium Kitchen & Bath Sealant Almond	Revision Date:	4/12/2022
Product UPC Number:	070798087859	Supercedes Date:	12/30/2021
Manufactured For	DAP Global Inc. 2400 Boston Street Suite 200 Baltimore, MD 21224-4723	Product Use/Class: SDS No:	Caulking Compound 9878504
	888-327-8477 (non - emergency matters) SDS Coordinator: MSDS@dap.com	Preparer:	Regulatory and Environmental Affairs
	Emergency Telephone: 1-800-535-5053, 1-352-323-3500, 1-800-222-1222		

2. Hazards Identification

EMERGENCY OVERVIEW: High concentration of vapors may cause irritation to eyes and respiratory system.

GHS Classification

Skin Sens. 1

Symbol(s) of Product



Signal Word Warning

Possible Hazards 7% of the mixture consists of ingredients of unknown acute toxicity

GHS HAZARD STATEMENTS

Skin Sensitizer, category 1

H317

May cause an allergic skin reaction.

SAP Number:

GHS LABEL PRECAUTIONARY STATEMENTS

P261	Avoid breathing dust/fume/gas/mist/vapours/spray.
P272	Contaminated work clothing should not be allowed out of the workplace.
P280	Wear protective gloves/protective clothing/eye protection/face protection.
P302+P352	IF ON SKIN: Wash with plenty of soap and water.
P321	Specific treatment (see on this label).
P333+P313	If skin irritation or rash occurs: Get medical advice/attention.
P501	Dispose of contents/container.
GHS SDS PRECAUTIONA	ARY STATEMENTS
P363	Wash contaminated clothing before reuse.

3. Composition/Information on Ingredients

Chemical Name	CAS-No.	<u>Wt. %</u>	GHS Symbols	GHS Statements
Silica, amorphous	7631-86-9		GHS07	H332
Methyltri(ethylmethylketoxime)silane	22984-54-9		GHS07-GHS08	H317-319-373

The text for GHS Hazard Statements shown above (if any) is given in the "Other information" Section.

4. First-aid Measures

FIRST AID - INHALATION: Material is not likely to present an inhalation hazard at ambient conditions. If you experience difficulty in breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

FIRST AID - SKIN CONTACT: Wash skin with soap and water for 15 minutes. Get medical aid if symptoms persist.

FIRST AID - EYE CONTACT: In case of contact, immediately flush eyes with large quantities of water for at least 15 minutes until irritation subsides. Get medical attention immediately.

FIRST AID - INGESTION: If swallowed, DO NOT INDUCE VOMITING. Get medical attention immediately.

5. Fire-fighting Measures

UNUSUAL FIRE AND EXPLOSION HAZARDS: No Information

SPECIAL FIREFIGHTING PROCEDURES: Wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear. Use water spray to cool exposed surfaces.

EXTINGUISHING MEDIA: Alcohol Foam, Carbon Dioxide, Dry Chemical, Foam, Water Spray or Fog

6. Accidental Release Measures

ENVIRONMENTAL MEASURES: No Information

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

7. Handling and Storage

HANDLING: KEEP OUT OF REACH OF CHILDREN!DO NOT TAKE INTERNALLY. Avoid breathing vapor and contact with eyes, skin and clothing. Use only with adequate ventilation. Wash thoroughly after handling. Remove contact lenses before using. Do not handle contact lenses until all sealant has been cleaned from fingertips, nails and cuticles. Residual sealant may transfer to contact lenses and cause severe eye irritation.

STORAGE: Avoid excessive heat and freezing. Do not store at temperatures above 120 °F (49 °C). Store away from caustics and oxidizers.

8. Exposure Controls/Personal Protection

Ingredients with Occupational Exposure Limits				
Chemical Name	ACGIH TLV-TWA	ACGIH-TLV STEL	<u>OSHA PEL-TWA</u>	OSHA PEL-CEILING
Silica, amorphous Methyltri(ethylmethylketoxime)silane	N.E. N.E.	N.E. N.E.	N.E. N.E.	N.E. N.E.

Further Advice: MEL = Maximum Exposure Limit OES = Occupational Exposure Standard SUP = Supplier's Recommendation Sk = Skin Sensitizer N.E. = Not Established

Personal Protection



RESPIRATORY PROTECTION: No personal respiratory protective equipment normally required.



SKIN PROTECTION: Wear nitrile or neoprene gloves.



EYE PROTECTION: Goggles or safety glasses with side shields.



OTHER PROTECTIVE EQUIPMENT: Not required under normal use.



HYGIENIC PRACTICES: Wash hands before breaks and at the end of workday. Remove and wash contaminated clothing before re-use.

9. Physical and Chemical Properties

Vapor Density: Heavier That	hed n n-Butyl Acetate
-----------------------------	--------------------------

Physical State: Odor Threshold: pH: Viscosity (mPa.s): Partition Coeff., n-octanol/water: Explosive Limits, %: Auto-Ignition Temperature, °C Vapor Pressure, mmHg: Flash Method: Flammability, NFPA: Paste Not Established Not Applicable Not Established Not Established Not Established Not Established Seta Closed Cup Non-Flammable

(See "Other information" Section for abbreviation legend) (If product is an aerosol, the flash point stated above is that of the propellant.)

10. Stability and Reactivity

STABILITY: This product is considered stable under normal and anticipated storage and handling conditions.

CONDITIONS TO AVOID: Oxidizing agents. Excessive heat and freezing.

INCOMPATIBILITY: Keep away from strong oxidizing agents. Incompatible with strong bases and oxidizing agents.

HAZARDOUS DECOMPOSITION PRODUCTS: Normal decomposition products, i.e., COx, NOx.

11. Toxicological Information

EFFECT OF OVEREXPOSURE - INHALATION: During application and cure, this product releases methanol. Inhalation may cause irritation to the respiratory tract (nose, mouth, mucous membranes). May cause allergic respiratory reaction.

EFFECT OF OVEREXPOSURE - SKIN CONTACT: Direct skin contact may cause irritation. May cause allergic skin reaction.

EFFECT OF OVEREXPOSURE - EYE CONTACT: May cause mild eye irritation.

SAP Number:

EFFECT OF OVEREXPOSURE - INGESTION: Single dose oral toxicity is very low. Amounts ingested incidental to industrial handling are not likely to cause injury; however, ingestion of large amounts may cause injury. Ingestion of large amounts may cause nausea, gastrointestinal upset, and pain. May cause liver and kidney damage, and central nervous system depression. Ingestion may result in obstruction when material hardens.

CARCINOGENICITY: No Information

EFFECT OF OVEREXPOSURE - CHRONIC HAZARDS: Repeated or prolonged exposure may cause mild irritation of eyes and skin. Repeated or prolonged skin contact may cause allergic reactions with susceptible persons. Constituents of this product include crystalline silica which ,if inhalable, may cause silicosis, a form of progressive pulmonary fibrosis. Inhalable crystalline silica is listed by IARC as a group I carcinogen (lung) based on sufficient evidence in occupationally exposed humans and sufficient evidence in animals. Crystalline silica is also listed by the NTP as a known human carcinogen. Constituents may also contain asbestiform or non-asbestiform tremolite or other silicates as impurities, and above de minimus exposure to these impurities in inhalable form may be carcinogenic or cause other serious lung problems.

PRIMARY ROUTE(S) OF ENTRY: Skin Contact, Inhalation

Acute Toxicity Values

The acute effects of this product have not been tested. Data on individual components are tabulated below

<u>CAS-No.</u>	<u>Chemical Name</u>	<u>Oral LD50</u>	<u>Dermal LD50</u>	<u>Vapor LC50</u>
7631-86-9	Silica, amorphous	7900 mg/kg Rat	≥5000 mg/kg Rabbit	N.I.
22984-54-9	Methyltri(ethylmethylketoxime)silane	>2453 mg/kg Rat	>2000 mg/kg Rat	>50 mg/L Rat

N.I. = No Information

12. Ecological Information

ECOLOGICAL INFORMATION: Ecological injuries are not known or expected under normal use.

13. Disposal Information

DISPOSAL INFORMATION: This product does not meet the definition of a hazardous waste according to U.S. EPA Hazardous Waste Management Regulation, 40 CFR Section 261. Dispose as hazardous waste according to all local, state, federal and provincial regulations. State and Local regulations/restrictions are complex and may differ from Federal regulations. Responsibility for proper waste disposal is with the owner of the waste. Do not flush into surface water or sanitary sewer system.

STEPS TO BE TAKEN IF MATERIAL IS RELEASED OR SPILLED: In case of spillage, absorb with inert material and dispose of in accordance with applicable regulations. Scrape up dried material and place into containers.

14. Transport Information

DOT UN/NA Number:	N.A.
DOT Proper Shipping Name: DOT Technical Name:	Not Regulated N.A.
DOT Hazard Class:	N.A.
Hazard SubClass:	N.A.
Packing Group:	N.A.

15. Regulatory Information

U.S. Federal Regulations:

CERCLA - SARA Hazard Category

This product has been reviewed according to the EPA 'Hazard Categories' promulgated under Sections 311 and 312 of the Superfund Amendment and Reauthorization Act of 1986 (SARA Title III) and is considered, under applicable definitions, to meet the following categories:

Respiratory or Skin Sensitization

SARA SECTION 313:

This product contains the following substances subject to the reporting requirements of Section 313 of Title III of the Superfund Amendment and Reauthorization Act of 1986 and 40 CFR part 372:

No Sara 313 components exist in this product.

TOXIC SUBSTANCES CONTROL ACT:

All ingredients in this product are either on TSCA inventory list, or otherwise exempt. This product contains the following chemical substances subject to the reporting requirements of TSCA 12(B) if exported from the United States:

No TSCA 12(b) components exist in this product.

16. Other Informat	ion		
Revision Date:		4/11/2022	Supersedes Date: 12/30/2021
Reason for revision:		Substance Hazard Threshold % Substance and/or Product Prop 01 - Product Information 08 - Exposure Controls/Person	perties Changed in Section(s):
Datasheet produced by:		Regulatory Depa	artment
HMIS Ratings:			
Health:	Flammability:	Reactivity:	Personal Protection:
2*	0	0	Х

VOC Less Water Less Exempt Solvent, g/L: 30.0

VOC Material, g/L: 30

VOC as Defined by California Consumer Product Regulation, Wt/Wt%: 2.89

VOC Actual, Wt/Wt%: 2.9

Text for GHS Hazard Statements shown in Section 3 describing each ingredient:

H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H373	May cause damage to organs through prolonged or repeated exposure.

Icons for GHS Pictograms shown in Section 3 describing each ingredient:



Legend: N.A. - Not Applicable, N.E. - Not Established, N.D. - Not Determined

DAP believes the data and statements contained herein are accurate as of the date hereof. They are offered in good faith as typical values and not as a product specification. NO WARRANTY OF MERCHANTABILITY, WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE OR ANY OTHER WARRANTY, EXPRESS OR IMPLIED, IS MADE WITH REGARD TO THE INFORMATION HEREIN PROVIDED OR THE PRODUCT TO WHICH THE INFORMATION REFERS. Since this document is intended only as a guide to the appropriate use and precautionary handling of the referenced product by a properly trained person, it is therefore the responsibility of the user to (i) review the recommendations with due consideration for the specific context of the intended use and (ii) determine if they are appropriate.