



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® DYNAGRIP® Tub Surround Construction Adhesive

PRODUCT DESCRIPTION

DAP® DYNAGRIP® TUB SURROUND construction adhesive is a premium grade, high strength adhesive specifically formulated for tub surround installation. This premium adhesive is safe for use on all tub surround materials and dries clear for an ideal finish. DYNAGRIP® TUB SURROUND is an instant grab adhesive that is moisture, steam, water, and heat resistance once fully cured.



PACKAGING	COLOR	UPC
10.3 fl oz (305 mL)	White	7079827521

KEY FEATURES & BENEFITS

- **Shower Safe - Safe to use on all tub surround and shower enclosure materials**
- **Dries Clear for an Ideal Finish - Goes on white and dries clear for an ideal finish**
- **Stronger Holding Power* – Powerful adhesion to hold panels in place**

*Stronger than competitive tub surround adhesives

PERFORMANCE CHARACTERISTICS

- Won't etch or burn tub surround material
- Instant grab
- Easy water clean up
- VOC compliant

SUGGESTED USES



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Adheres to:

- ABS Tub Surrounds
- Acrylic Tub Surrounds
- Cement Backerboard
- Ceramic Tiles
- Dimensional Lumber
- Drywall
- Fiberglass Tub Surrounds
- Foamback Tub Surrounds
- Greenboard
- OSB
- Plywood
- PVC Tub Surrounds

Recommended for:

- Tub Surround Installation
- Shower Wall Enclosures

Not Recommended for:

- Mirror installation
- Bonding two non-porous materials
- Applications other than tub surround & water enclosure installation

FOR BEST RESULTS

- Apply in temperatures above 40°F. Keep adhesive above 40°F for easier gunning.
- One surface must be porous.
- Store away from extreme heat or cold

APPLICATION

1. Surfaces must be clean, structurally sound, and free of debris.
2. Pre-cut and fit materials before applying adhesive.
3. Trim nozzle to desired bead size. 1/4" recommended for most applications.
4. Puncture inner foil seal.
5. Load cartridge into applicator gun.
6. Apply a continuous bead to studs or backer substrate, adhesive may also be applied to back of tub surround panel according to tub surround manufacturers installation instructions.
7. Within 10 minutes, position and press panels firmly into place.
8. Allow to dry for 24 hours before exposing to water or moisture.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Typical Uncured Physical Properties	
Appearance/Consistency	Smooth paste
Base Polymer:	Synthetic latex
Bead Color	White
Weight % Solids	51%



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Odor	Mild
Clean Up	Soap & water
Flash Point	212°F
Shelf Life	18 months
Coverage	10oz: ¼" bead yields 32 linear ft, 3/8" bead yields 14 linear ft 28oz: ¼" bead yields 86 linear ft, 3/8" beach yields 38 linear ft
Typical Application Properties	
Application Temperature Range:	40°F – 100°F
Tooling Time (Working Time)	20 minutes
Full Cure Time	7 days
Typical Cured Performance Properties	
Service Temperature Range:	0°F – 140°F
Gap Bridging	N/A
VOC Content	< 50g/L
Calif. ARB VOC	<1% Wt/Wt

CLEAN UP & STORAGE

Uncured adhesive: wash away with warm water and soap. Cured adhesive: must be cut or scraped away.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **1-888-DAP-TIPS**.

WARRANTY

DAP will provide replacement product or refund sales price if product fails to perform when used as directed. Call 1-888-DAP-TIPS, with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Usage Information: Call **1-888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com