



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® RapidFuse® BlueStik™ Adhesive Putty

PRODUCT DESCRIPTION

DAP® RapidFuse® BlueStik™ is a reusable, removable adhesive putty that replaces tape, tacks, staples, and magnets. It is ideal for a wide variety of uses in the home, school and office. It can be used time and time again and won't dry out. No more chipped, peeled paint or holes in the walls. This convenient, ready-to-use putty bonds just about anything to slick or hard surfaces, such as wood, tile, glass, concrete, porcelain, high pressure laminate, metal and painted surfaces. Use to fasten decorations, posters, notes and paintings. Also helps protect items from vibration damage. BlueStik can be used time and time again. Conforms to ASTM D 4236.



| PACKAGING | COLOR | UPC |
|---------------|-------|------------|
| 1.0 OZ (28 g) | Blue | 7079801201 |

KEY FEATURES & BENEFITS

- Replaces tape & tacks
- Removable
- No mess
- Non-toxic
- For hanging posters, photos & drawings



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

SUGGESTED USES

Ideal for all types of hobby and craft, school, office and around the home uses.

- Level picture hanging picture frames.
- Secure collectibles.
- Keep cords and cables in place.
- Hold needles.
- Hold hooks and fishing lures.
- Temporarily hold items in place while liquid glue dries.

Use to mount or hang:

- Posters
- Photos
- Drawings
- Cards
- Decorations
- Notes

Adheres to a wide variety of surfaces such as:

- Wood
- Tile
- Glass
- Concrete
- Porcelain
- Fabrics
- Metal
- Paper
- Styrofoam
- Plastic
- Vinyl
- Plastic Laminate
- High Pressure Laminates
- Painted Surfaces

APPLICATION

1. DAP RapidFuse® BlueStik should be applied to clean, dry surfaces at room temperature (68-72°F, 21-23°C).
2. To use, tear off enough BlueStik Reusable Adhesive Putty for the job.
3. Roll into a ball until it becomes soft and tacky.
4. Place adhesive between the surfaces to be fastened and press firmly.
5. **CAUTION:** BlueStik may leave an oily residue on some surfaces (e.g. flat latex painted drywall). Check by applying BlueStik in an inconspicuous place for 24 hours, then lift.
6. If a stain does occur, it can usually be removed with Isopropyl (rubbing) alcohol. Do not use BlueStik™ on soft flocked or loose wallpaper, newly painted surfaces, loose paint, or for hanging heavy objects such as mirrors and framed pictures. Not for exterior applications. If BlueStik™ residue should remain on surface, roll BlueStik™ into a ball and roll over residue.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

| | |
|--------------------------------|--------------------------------|
| Adhesive Base: | Synthetic rubber |
| Consistency: | Pliable |
| Volatile: | <1% |
| Non-Volatiles: | 99% |
| Viscosity: | Not Applicable |
| Flash Point: | Not Applicable |
| Weight/Gallon: | 14.9 lbs/gal |
| Odor: | Negligible |
| Application Temperature Range: | 40°F to 105°F |
| Optimum Storage Temperature: | 55°F to 85°F |
| Service Temperature Range: | 40°F to 105°F |
| Handling Time: | Instant |
| Full Cure: | Permanent tacky |
| Freeze/Thaw Stability: | Stable |
| Coverage: | 7.6 sq. in. @ 1/8 in thickness |
| Appearance: | Blue |
| Shelf Life: | 1 Year, minimum |

CLEAN UP & STORAGE

This product may leave an oily residue on some surfaces. Prior to use, check by applying product in an inconspicuous place for 24 hours, then remove. If a stain does occur, it can usually be removed with a solvent like Isopropyl (rubbing alcohol). If BlueStik™ residue should remain on surface, roll BlueStik™ into a ball and roll over residue.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

LIMITED WARRANTY: If product fails to perform when used as directed, within one year from the date of purchase, call **888-DAP-TIPS**, with your sales receipt and product container available, for replacement product or sales price refund. DAP will not be liable for incidental or consequential damages.



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com