



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® TankBond® Thread Stopper™

### PRODUCT DESCRIPTION

DAP® TankBond® **No More Loose Screws!** Tank Bond™ Thread Stopper™ holds screw and bolts tightly in place. The fast-dry coating creates a tight seal that absorbs shock and vibrations preventing fasteners from unintentionally backing out of wood, metal, and plastic. Simply apply Thread Stopper to screw threads, let it dry, and install the screw into place. Treated fasteners remain completely adjustable, removable or reusable.



PACKAGING	COLOR	UPC
.2 fl oz (6 mL) tube	Red	7079800167

### KEY FEATURES & BENEFITS

- No Locking
- Easy to Remove
- Easy to Use Formula

### PERFORMANCE CHARACTERISTICS

- Absorbs Shock and Vibrations
- Remove & Reuse up to 5x
- Multi Material: Wood, Metal, Plastic, & More



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## SUGGESTED USES

Can be used to prevent fasteners from loosening on furniture, door knobs, hinges, Eyewear frames, etc.

Ideal for Bonding:

- Metal
- Plastic
- Wood

## APPLICATION

### **Surface Preparation:**

1. Wear gloves to avoid skin contact.
2. Ensure parts are clean, dry and free from oil, grease, and foreign materials.
3. Shake tube to mix solution before applying.
4. Remove cap and then cut tip as desired.

### **Application:**

1. Apply liquid to threaded surface, filling threads entirely. Temperature must be between 40°F to 120°F for application.
2. Allow liquid coating to dry for 30 minutes.
3. Thread on nut and apply gel to either side of threaded component.

Note: It is recommended that DAP Tank Bond Thread Stopper be tested in the application for which it is to be used.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Adhesive Base:	Acrylic Resins
Consistency:	Viscous liquid
Color:	Red
Non-Volatiles:	75%
Flash Point:	60.8 °F
Weight/Gal:	9.07 lbs/gal
Application Temperature Range:	40°F to 120°F
Service Temperature Range:	-65°F to 165°F
Full Cure (for assembly):	30 mins
Shelf Life:	24 Months Minimum @ 70°F



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## CLEAN UP & STORAGE

Keep container closed when not in use. Keep product away from all sources of ignition, heat or flame. Store product in a cool, dry place.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at [dap.com](http://dap.com) or calling 888-DAP-TIPS.

## WARRANTY

LIMITED WARRANTY: If product fails when used as directed, within one year of purchase, DAP will provide replacement product or refund sales price: call (888) DAP TIPS with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call **888-DAP-TIPS** or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**