



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## DAP® RAPIDFUSE® All Purpose Spray Adhesive

### PRODUCT DESCRIPTION

**DAP RAPIDFUSE All Purpose Spray Adhesive** is a mist spray formula that can be used for the temporary or permanent bonding of lightweight materials including carpeting, foils, many plastics, papers, felt, foams, metals and cardboard.



PACKAGING	COLOR	UPC
11 OZ. NET. WT	Clear	7079800114

### KEY FEATURES & BENEFITS

- Mist spray
- Provides a temporary or permanent bond
- Ideal for hobby & craft applications
- Interior/exterior Formula.

### SUGGESTED USES

Ideal for use on:

- Trim work
- Upholstery Work

Adheres to:

- Foils
- Plastics
- Papers
- Carpeting
- Foams
- Felt
- Metals
- Cardboard



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## APPLICATION

- 1. SAFETY FIRST! PRODUCT IS EXTREMELY FLAMMABLE WHILE DISPENSING! READ AND UNDERSTAND ALL OF THE PRECAUTIONARY MEASURES FOR USE, HANDLING, STORAGE AND DISPOSAL CONTAINED IN THE PRODUCT LABEL AND SAFETY DATA SHEET (SDS).**
2. Extinguish all ignition sources during use and cure.
3. Be sure surfaces to be bonded are clean, dry, and free of all foreign material.
4. Wear safety glasses and use in well-ventilated areas.
5. Shake can 1-2 minutes before use.
6. Remove red applicator lock from spray can by sliding upwards and discarding.
7. Hold can 6-8 inches from the surface to be sprayed.
8. Keep can moving while spraying to get an even film of adhesive on the surface to be bonded.
9. Make bond while the adhesive is aggressively tacky 1-10 minutes after applying.
10. Press objects together firmly across the entire surface.
11. **For Temporary Bonds:** Spray one surface and allow to dry up to 30 minutes.
12. **For Permanent Bonds:** Spray both surfaces and allow to dry up to 2 hours.
13. **Maximum Open Time:** 1-sided application: 30 minutes. 2-sided application: 2 hours.

**AFTER USE:** Invert can and depress spray tip until spray is free of adhesive. Store glued assembly out of direct sunlight and in stable conditions until fully dried (approximately 24 hours). If the spray tip becomes clogged, clean with a mineral spirits or acetone.

## TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Adhesive Base:	Synthetic Rubber
Volatile:	Organic solvent
Application Temperature:	60°F to 80°F
Service Temperature Range:	0°F to 150°F
Coverage:	Approximately 68 sq. ft. per can on a single surface. Coverage will vary depending on porosity of substrates.
Odor:	Solvent
Freeze Thaw Stability:	Stable
Shelf Life:	12 months



# TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

## CLEAN UP & STORAGE

Clean excess wet adhesive from surfaces and tools with mineral spirits. Dried adhesive must cut or scraped away. Clean hands with warm water and soap. DO NOT use solvents to remove product from skin. Store container in cool, dry place away from extreme heat or cold.

## SAFETY

See product label or Safety Data Sheet (SDS) for health and safety information. You can request an SDS sheet by calling 888-DAP-TIPS or by visiting our website at [dap.com](http://dap.com).

## WARRANTY

LIMITED WARRANTY: If product fails when used as directed within one year of purchase, DAP will provide replacement product or refund sales price: call 888-DAP-TIPS with your sales receipt and product container available, to arrange for warranty fulfillment. DAP is not liable for incidental or consequential damages.

## COMPANY IDENTIFICATION

**Manufacturer:** DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

**Usage Information:** Call **888-DAP-TIPS** or visit [dap.com](http://dap.com) & click on "Ask the Expert"

**Order Information:** 800-327-3339 or [orders@dap.com](mailto:orders@dap.com)

**Fax Number:** 410-558-1068

**Also, visit the DAP website at [dap.com](http://dap.com)**