



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

DAP® Wall Repair Patch Kit with DRYDex® Spackling

PRODUCT DESCRIPTION

DAP® Wall Repair Patch Kit featuring DRYDex® Dry Time Indicator Spackling comes with all of the tools needed to complete a wall-patching project. This kit may be used to repair holes up to 3 inches in diameter in drywall, plaster or masonry surfaces. DRYDex Spackling provides a unique dry-time indicator that verifies when the patched surface is ready to be sanded and painted.



PACKAGING	COLOR	UPC
<p>1 Ea. - .5 pt.</p> <ul style="list-style-type: none"> 1 – 8 oz. tub of DRYDex Spackling 1 - 5" x 5" Fiber Tough Wall Patch 1- 4" x 3" 100 grit sand paper 1- 2" ergonomic plastic putty knife 	Pink to White	7079812345

KEY FEATURES & BENEFITS

- For the quick and easy repair of holes and cracks
- Includes all the necessary tools
- Unique Dry Time Indicator Spackling eliminates errors
- Repairs holes up to 3" in diameter
- Interior use

SUGGESTED USES

Ideal for filling holes, cracks and defects on:

- Drywall
- Plaster



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

FOR BEST RESULTS

- Do not apply when temperatures are below 50°F.
- Do not apply outside if rain is expected within 24 hours.
- Do not use on floors or as a caulk, sealant or joint filler over cracks and joints where expansion and contraction may occur.
- DO NOT USE AS A SKIM COAT.
- For exterior applications, always topcoat with a good-quality exterior grade paint.
- Do not use for tuck pointing applications on brick

APPLICATION

1. Make sure the area to be repaired is clean, dry, firm and free of any loose debris or materials.
2. Using enclosed putty knife, apply the DRYDex Spackling to the back of the patch. If necessary, this patch can be cut with a regular pair of scissors to fit smaller holes or cracks. Press the patch against the surface to be repaired. Press firmly around the outer edges of the patch to ensure a strong bond.
3. Using the enclosed putty knife, spread the DRYDex Spackling over the patch and adjacent area. Make sure to feather edge the patch.
4. Spackling Compound will change color from pink to white when the surface is ready to be sanded & painted.
5. Once spackling compound is completely dry, use the enclosed sandpaper and sand the patched area to a smooth finish.
6. Apply a second finishing coat if necessary following the instructions above.
7. Paint the patched surface as desired.

NOTE: To retain the effectiveness of the dry time indicator, keep the container tightly closed after use.

TYPICAL PHYSICAL & CHEMICAL PROPERTIES

Consistency:	Paste
Vehicle:	Latex Polymer
Volatile:	Water
Filler:	Inert Filler
Odor:	Mild
Weight/Gallon:	15.6 lbs.
Solids:	77% by weight
Application Temperature:	50° F Minimum
Service Temperature:	0°F to 150°F
Shelf Life:	12 months
Freezing:	Freeze/Thaw Stable 5 Cycles at 0°F



TECHNICAL DATA SHEET

2400 Boston Street | Suite 200 | Baltimore, MD | 21224

Drying Time:	1 to 5 hours depending on temperature, relative humidity and depth of fill.
Painting:	Takes either oil or latex-based paint

CLEAN UP & STORAGE

Wash tools immediately after use with water before product has set. Dried material must be mechanically scraped, chipped or ground away. Close container tightly and store any remaining powder in a cool, dry place.

SAFETY

See product label and Safety Data Sheet (SDS) for health and safety information. You can request an SDS by visiting our website at dap.com or by calling **888-DAP-TIPS**.

WARRANTY

Limited Warranty:

If product fails to perform when used as directed, within one year of date of purchase, call 888-DAP-TIPS, with your sales receipt and product container available, for replacement product or sales price refund. DAP Products, Inc. will not be responsible for incidental or consequential damages.

COMPANY IDENTIFICATION

Manufacturer: DAP Products Inc., 2400 Boston Street, Baltimore, Maryland 21224

Usage Information: Call **888-DAP-TIPS** or visit dap.com & click on "Ask the Expert"

Order Information: 800-327-3339 or orders@dap.com

Fax Number: 410-558-1068

Also, visit the DAP website at dap.com